

目录 Catalogue


压铆螺母系列 SELF CLINCHING NUTS

	S / CLS / SP 压铆螺母【SELF CLINCHING NUTS】	7
	BOB / BOSO 六角压铆螺母【HEXAGON SELF CLINCHING NUTS】	8
	BN / BNS 六角斜花螺母【HEXAGON DIAGONAL NUTS】	8
	Z / ZS 涨铆螺母【FLARE IN NUTS】	9
	NZ / NZS 六角涨铆螺母【HEXAGON FLARE IN NUTS】	10
	KFS2 挤压螺母【BROACHING NUTS】	10
	F / F4 齐平螺母【FLUSH NUTS】	11
	AS / AC / LAS / LAC 浮动压铆螺母【FLOATING NUTS】	12
	SL 自锁螺母【LOCKING NUTS】	13
	PL / PLC 防松自锁螺母【SELF LOCKING NUTS】	14
	LK / LKS 压铆自锁螺母【SELF LOCKING NUTS】	15
	U / UL / FE / FEO / FEX / FEOX 微型螺母【SELF LOCKING NUTS】	16

压铆螺钉 SELF CLINCHING STUDS

	FH / FHS / FHA 压铆螺钉【SELF CLINCHING STUDS】	17
	FH4 压铆螺钉【SELF CLINCHING STUDS】	18
	FH / FHS / FHA 压铆销钉【FLUSH HEAD PINS】	19
	TFH / TFHS 非平头压铆螺钉【NON FLUSH SELF CLINCHING STUDS】	20
	FHL / FHLS 小头窄型压铆螺钉【LOW-DISPLACEMENT HEAD STUDS】	21
	HFH / HFHS / HFHB 重载压铆螺钉【HIGH STRENGTH CLINCHING STUDS】	21
	HFE / HFES 薄板重载螺钉【HEAVY DUTY SELF CLINCHING STUDS】	22
	KFH 挤压螺钉【BROACHING STUDS】	22
	FE / FES 焊接螺钉【WELD STUDS】	23
	NFH / NFHS 六角螺钉【HEXAGON SELF CLINCHING STUDS】	23
	CHC / CHA / CFHA / CFHC 埋头螺钉【CONCEALED-HEAD STUD】	24

压铆螺柱 SELF CLINCHING STANDOFFS

	BSO / BSOS / BSOA / BSO4 盲孔压铆螺柱【SELF CLINCHING STANDOFFS】	25
	SO / SOS / SOA / SO4 通孔压铆螺柱【SELF CLINCHING STANDOFFS】	26
	DSO / DSOS / DSOA / DSO4 / DSOB 花齿压铆螺柱【SELF CLINCHING STANDOFFS】	27
	BSS 无台阶防水螺母柱【BLIND STANDOFFS】	27
	B / BS / BS4 防水螺母柱【BLIND STANDOFFS】	28
	ITS / IT 种焊螺柱【WELD STANDOFFS】	29
	TBSO / TBSOS / TBSOA 反盲孔压铆螺柱【ANTI BLIND HOLE STANDOFFS】	29
	CSOS / CSS 埋头螺柱【CONCEALED HEAD STANDOFFS】	30
	SSS / SSC / SSA 支撑卡柱【SNAP TOP STANDOFFS】	31
	KSSB 支撑卡柱【SNAP TOP STANDOFFS】	31
	SKC 定位支撑柱【KEYHOLE STANDOFFS】	32
	TPS/TP4 压铆定位销【PILOT PINS】	32
	MPP 微型定位销【PILOT PINS】	33

面板螺丝 CAPTIVE SCREW



	PF09 / PF10 面板螺丝【CAPTIVE SCREW】	34
	PF11 / PFS11 / PF12 / PF114 / PFS114 / PFG11 面板螺丝【CAPTIVE SCREW】	35
	PF11MF / PF12MF 面板螺丝【CAPTIVE SCREW】	36
	PF11MW / PF12MW 面板螺丝【CAPTIVE SCREW】	37
	PF15(41) / PF25(42) / PFS15(41) / PFS25(42) 面板螺丝【CAPTIVE SCREW】	38
	PF21 / PF22 面板螺丝【CAPTIVE SCREW】	39
	PF30 / PF31 / PF32 / PFS30 / PFS31 / PFS32 面板螺丝【CAPTIVE SCREW】	40
	PF50/51/52 / PF60/61/62 / PFS50/51/52 / PFS60/61/62 面板螺丝【CAPTIVE SCREW】	41
	PF16 / PF26 / PF51 / PF52 面板螺丝【CAPTIVE SCREW】	42
	PFC2 / PFS2 面板螺丝【CAPTIVE SCREW】	43
	PFC2P 面板螺丝【CAPTIVE SCREW】	44
	PFHV 面板螺丝【CAPTIVE SCREW】	45
	FC 面板螺丝【CAPTIVE SCREW】	46

	PTL2 / PTLS2 弹簧定位销【LOCATING PIN, SPRING LOADED】	47
	PT-56-61 弹簧定位销【LOCATING PIN, SPRING LOADED】	47
	TD / TDS 电缆扎带固定座/压铆线扣【CABLE TIE-MOUNTS】	48
	RAS 直角压铆线扣【CABLE TIE-MOUNTS】	49
	SMTSO / SMTSOB SMT螺母【SURFACE MOUNT NUTS】	50
拉铆螺母 RIVRT NUTS		
	FH.KB 平头菊花竖条纹Flat Head Knurled Body	51
	RH.KB 小沉头竖条纹 Reduce Head Knurled Body	51
	FH-SHB 平头半六角Flat Head Semi-Hex Body	52
	RHH-IHB-UK 小沉头内外六角Reduce Hex Head Inner-Hex Body-UK	52
	CH-KB 大沉头菊花竖条纹Countersunk Head Knurled Body	53
	FH-KB-AVK 平头（菊花）竖条纹（美标）Flat Head Knurled Body-AVK	53
	FH-KBC 平头竖条纹（盲孔）Flat Head Knurled Body Close End	58
	FH-FHB 平头全六角 Flat Head Full Hex Body	59

压铆螺母 【SELF CLINCHING NUTS】

产品型号分解 Part Number Designation

CLS - **M2** - **1** **ZI**
 ↓ ↓ ↓ ↓
 Type and Thread Shank Finish
 Material Cold Code



尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE			螺纹码 Thread Code	底端码 Shank Code	安装孔 Hole Size In Sheet	最小板厚 Min.Sheet Thickness	A (Shank) Max.	C Max.	E ±0.25	T ±0.25	最小边距 Min. Dist. Hole C/L To Edge
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron									
	M2*0.4	S	CLS	SP	M2	0 1 2	4.25	0.8-1 1 1.4	0.77 0.97 1.38	4.22	6.3	1.5	4.8
	M2.5*0.45	S	CLS	SP	M2.5	0 1 2	4.25	0.8-1 1 1.4	0.77 0.97 1.38	4.22	6.3	1.5	4.8
	M3*0.5	S	CLS	SP	M3	0 1 2	4.25	0.8-1 1 1.4	0.77 0.97 1.38	4.22	6.3	1.5	4.8
	M3.5*0.6	S	CLS	SP	M3.5	0 1 2	4.75	0.8-1 1 1.4	0.77 0.97 1.38	4.73	7.1	1.5	5.6
	M4*0.7	S	CLS	SP	M4	0 1 2	5.4	0.8-1 1 1.4	0.77 0.97 1.38	5.38	7.9	2	6.9
	M5*0.8	S	CLS	SP	M5	0 1 2	6.4	0.8-1 1 1.4	0.77 0.97 1.38	6.38	8.7	2	7.1
	M6*1	S	CLS	SP	M6	0 1 2 3	8.75	1.2 1.4 2.3 3.18	1.15 1.38 2.21 3.05	8.72	11.05	4.08	8.6
	M8*1.25	S	CLS	SP	M8	0 1 2 3	10.5	1.2 1.4 2.3 3.18	1.15 1.38 2.21 3.05	10.47	12.65	5.47	9.7
	M10*1.5	S	CLS	SP	M10	0 1 2 3	14	1.7 2.31 3.18 4	1.61 2.21 3.05 3.84	13.97	17.35	7.48	13.5
	M12*1.75	S	CLS	SP	M12	0 1 2	17	2.5 3.18 6.1	1.95 3.05 5.80	16.97	20.05	8.5	18

尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED(英制)	螺纹尺寸 Thread Size	型号TYPE			螺纹码 Thread Code	底端码 Shank Code	安装孔 Hole Size In Sheet	板厚 Min.Sheet Thickness	A (Shank) Max.	C Max.	E ±0.10	T ±0.10	最小边距 Min. Dist. Hole C/L To Edge
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron									
	.086-56 (#2-56)	S	CLS	SP	256	0 1 2	.166	.030 .040 .056	.030 .038 .054	.166	.25	.07	.19
	.099-48 (#3-48)	S	CLS	SP	348	0 1 2	.166	.030 .040 .056	.030 .038 .054	.166	.25	.07	.19
	.112-40 (#4-40)	S	CLS	SP	440	0 1 2 3	.166	.030 .040 .056 .091	.030 .038 .054 .087	.166	.25	.07	.19
	.138-32 (#6-32)	S	CLS	SP	632	0 1 2 3	.1875	.030 .040 .056 .091	.030 .038 .054 .087	.1857	.28	.07	.22
	.164-32 (#8-32)	S	CLS	SP	832	0 1 2 3	.213	.030 .040 .056 .091	.030 .038 .054 .087	.213	.31	.09	.27
	.190-24 (#10-24)	S	CLS	SP	024	0 1 2 3	.250	.030 .040 .056 .091	.030 .038 .054 .087	.250	.34	.09	.28
	.190-32 (#10-32)	S	CLS	SP	032	0 1 2 3	.250	.030 .040 .056 .091	.030 .038 .054 .087	.250	.34	.09	.28
	.216-24 (#12-24)	S	CLS	SP	1224	0 1 2 3	.277	.030 .040 .056 .091	.030 .038 .054 .087	.277	.38	.13	.31
	.250-20 (1/4-20)	S	CLS	SP	0420	0 1 2 3	.344	.047 .056 .091 .125	.045 .054 .087 .120	.344	.44	.17	.34
	.250-28 (1/4-28)	S	CLS	SP	0428	0 1 2 3	.344	.047 .056 .091 .125	.045 .054 .087 .120	.344	.44	.17	.34
	.313-18 (5/16-18)	S	CLS	SP	0518	0 1 2 3	1.000	.056 .091 .125 .156	.054 .087 .120 .156	.413	.50	.23	.38
	.313-24 (5/16-24)	S	CLS	SP	0524	0 1 2 3	.413	.056 .091 .125 .156	.054 .087 .120 .156	.413	.50	.23	.38
	.375-16 (3/8-16)	S	CLS	SP	0616	0 1 2 3	.500	.091 .125 .250 .375	.087 .120 .235 .375	.500	.56	.27	.44
	.375-24 (3/8-24)	S	CLS	SP	0624	0 1 2 3	.500	.091 .125 .250 .375	.087 .120 .235 .375	.500	.56	.27	.44
	.500-13 (1/2-13)	S	CLS	SP	0813	0 1 2	.656	.125 .250 .375	.120 .235 .375	.656	.81	.36	.63
	.500-20 (1/2-20)	S	CLS	SP	0820	0 1 2		.125 .250 .375	.120 .235 .375				

六角压铆螺母【HEXAGON SELF CLINCHING NUTS】



产品型号分解 Part Number Designation

BOBS - M3 - 1

↓ ↓ ↓

Type and Thread Shank

Material Cold Code



尺寸单位: MM

All Dimensions are in Millimeters

螺纹尺寸* 螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A (Shank) Max.	板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C Max.	E ±0.25	T ±0.25	最小边距 Min. Dist. Hole C/L To Edge
	碳钢 Carbon Steel	不锈钢 Stainless Steel									
M3*0.5	KD-BOB	KD-BOBS	M3	0	0.8	0.8	4.25	4.22	5.5	2	4.8
				1	1	1					
				2	1.35	1.4					
M4*0.7	KD-BOB	KD-BOBS	M4	0	0.8	0.8	5.4	5.38	7.0	2.2	6.9
				1	1	1					
				2	1.35	1.4					
M5*0.8	KD-BOB	KD-BOBS	M5	0	0.8	0.8	6.4	6.38	8.0	3	7.1
				1	1	1					
				2	1.35	1.4					
M6*1	KD-BOB	KD-BOBS	M6	1	1.15	1.2	8.75	8.72	10	4	8.6
				2	1.4	1.5					
				2	1.4	1.5					
M8*1.25	KD-BOB	KD-BOBS	M8	1	1.15	1.2	10.5	10.47	12.7	5	9.7
				2	1.4	1.5					
				2	1.4	1.5					

六角斜花螺母【HEXAGON DIAGONAL NUTS】



产品型号分解 Part Number Designation

BN M3 -1

↓ ↓ ↓

Type and Thread Shank




Material Cold Code



尺寸单位: MM All Dimensions are in Millimeters											
METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	底端码 Shank Code	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	A Max	C ±0.1	H ±0.25	T	最小边距 Min. Dist. Hole C/L To Edge
	M3*0.5	BN	M3	1	1	4.5	0.9	4.7	5.5	2.1	5.6
				2	2		1.8			1.2	
	M4*0.7	BN	M4	1	1	5.5	0.9	5.7	7	2.3	7.0
				2	2		1.8			2.7	
	M5*0.8	BN	M5	1	1	6.5	0.9	6.75	8	3.1	8.0
				2	2		1.8			3.2	
	M6*1.0	BN	M6	1	1	8	0.9	8.25	10	4.1	8.7
				2	2		1.8			3.2	
	M8*1.25	BN	M8	2	2	10	1.8	10.35	13	4.7	9.5
	M10*1.5	BN	M10	2	2	12.5	1.8	12.85	15	6.2	
	M12*1.75	BN	M12	2	3	14.5	2.8	14.85	17	7.2	1.0

涨铆螺母【FLARE IN NUTS】

产品型号分解 Part Number Designation



尺寸单位：MM
All Dimensions are in Millimeters

圆 形 涨 铆 螺 母 (ROUND FLARE IN NUTS)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A ±0.1	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	C Max	E ±0.25	T ±0.25
		碳钢 Carbon Steel	不锈钢 Stainless Steel								
	M3*0.5	Z	ZS	M3	1 1.2 1.5 2 2.5	1 1.2 1.5 2 2.5	1 1.2 1.5 2 2.5	5	4.98	7	3
	M4*0.7	Z	ZS	M4				6	5.98	8	4
	M5*0.8	Z	ZS	M5				8	7.95	10	5
	M6*1	Z	ZS	M6				9	8.98	11	6
	M8*1.25	Z	ZS	M8				11	10.98	13	6
	M10*1.5	Z	ZS	M10	2	2	2	14	13.9	16	8
					3	3	3				


尺寸单位：英寸
All Dimensions are in Inches

六 角 形 涨 铆 螺 母 (HEXAGON FLARE IN NUTS)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A ±0.1	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	C Max	E ±0.25	T ±0.25
		碳钢 Carbon Steel	不锈钢 Stainless Steel								
	M3*0.5	ZM	ZMS	M3	1.5	1.5	1.5	5	4.98	6	3
					2	2	2				
	M4*0.7	ZM	ZMS	M4	1.5	1.5	1.5	6	5.98	7	4
					2	2	2				
					3	3	3				
	M5*0.8	ZM	ZMS	M5	2	2	2	8	7.95	9	5
					3	3	3				
	M6*1	ZM	ZMS	M6	3	3	3	9	8.98	10	6
					4	4	4				
					5	5	5				
					6	6	6				
	M8*1.25	ZM	ZMS	M8	3	3	3	11	10.98	12.7	6
					4	4	4				
					5	5	5				
					6	6	6				
	M10*1.5	ZM	ZMS	M10	2	2	2	14	13.9	16	8
					3	3	3				
	M12*1.75	ZM	ZMS	M12	2	2	2	16	15.9	17	10
					3	3	3				

六角涨铆螺母【HEXAGON FLARE IN NUTS】

产品型号分解 Part Number Designation

NZS - M3 - 1
↓ ↓ ↓
Type and Material Thread Code Shank Code




尺寸单位: MM
All Dimensions are in Millimeters

螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A ±0.1	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C Max	E ±0.25	T ±0.1
	碳钢 Carbon Steel	不锈钢 Stainless Steel								
M3*0.5	NZ	NZS	M3	1.5	1.5	1.5	5	4.98	6	3
				2	2	2				
M4*0.7	NZ	NZS	M4	1.5	1.5	1.5	6	5.98	7	4
				2	2	2				
				3	3	3				
M5*0.8	NZ	NZS	M5	2	2	2	8	7.95	9	5
				3	3	3				
M6*1	NZ	NZS	M6	3	3	3	9	8.98	10	6
				4	4	4				
				5	5	5				
				6	6	6				
M8*1.25	NZ	NZS	M8	3	3	3	11	10.98	12.7	6
				4	4	4				
				5	5	5				
				6	6	6				

挤压螺母【BROACHING NUTS】

产品型号分解 Part Number Designation

KFS2 - M3
↓ ↓
Type and Material Thread Code



型号 TYPE	螺纹尺寸 Thread Size	A	板厚 Sheet Thickness	安装孔 Hole Size In Sheet	C	E	T	最小边距 Min.Dist. Hole C/L To Edge
		柄长		0.08				
KFS2	M2*0.4	1.53	1.53	3.73	4.19	5.56	1.5	4.2
	M2.5*0.45	1.53	1.53	4.22	4.68	5.56	1.5	4.4
	M3*0.5	1.53	1.53	4.22	4.68	5.56	1.5	4.4
	M4*0.7	1.53	1.53	6.4	6.86	8.74	2	6.4
	M5*0.8	1.53	1.53	6.9	9.53	9.53	3	7.1


齐平螺母【FLUSH NUTS】

产品型号分解 Part Number Designation

F - M2 - 1

↓ ↓ ↓

Type and Material Thread Cold Shank Code



尺寸单位: MM
All Dimensions are in Millimeters



螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	安装孔 Hole Size In Sheet	板厚 Sheet Thickness	A (Shank) Max.	C Max	H Nom.	最小边距 Min. Dist. Hole C/L To Edge
	不锈钢 Stainless Steel	不锈钢 Stainless Iron								
M2*0.4	F	F4	M2	1	4.37	1.53-2.3	1.53	4.35	4.8	6
				2		2.32-UP	2.3			
M2.5*0.45	F	F4	M2.5	1	4.37	1.53-2.3	1.53	4.35	4.8	6
				2		2.32-UP	2.3			
M3*0.5	F	F4	M3	1	4.37	1.53-2.3	1.53	4.35	4.8	6
				2		2.32-UP	2.3			
M4*0.7	F	F4	M4	1	7.37	1.53-2.3	1.53	7.35	7.9	7.2
				2		2.32-UP	2.3			
M5*0.8	F	F4	M5	1	7.92	1.53-2.3	1.53	7.92	8.7	8
				2		2.32-UP	2.3			
M6*1	F	F4	M6	3	8.74	3.18-3.94	3.05	8.74	9.5	8.8
				4		3.96-4.72	3.84			
				5		4.75-UP	4.63			

UNIFIED (英制)

尺寸单位: 英寸 All Dimensions are in Inches										
螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	安装孔 Hole Size In Sheet	板厚 Sheet Thickness	A (Shank) Max.	C Max	H Nom.	最小边距 Min. Dist. Hole C/L To Edge
	不锈钢 Stainless Steel	不锈钢 Stainless Iron								
.086-56 (#2-56)	F	F4	256	1	.172	.060-.090	.060	.171	.188	.23
				2		.091-UP	.090			
.112-40 (#4-40)	F	F4	440	1	.172	.060-.090	.060	.171	.188	.23
				2		.091-UP	.090			
.138-32 (#6-32)	F	F4	632	1	.213	.060-.090	.060	.212	.250	.27
				2		.091-UP	.090			
.164-32 (#8-32)	F	F4	832	1	.290	.060-.090	.060	.289	.312	.28
				2		.091-UP	.090			
.190-24 (#10-24)	F	F4	032	1	.312	.060-.090	.060	.311	.343	.31
				2		.091-UP	.090			
.250-20 (1/4-20)	F	F4	0420	3	.344	.125-.155	.120	.343	.375	.34
				4		.156-.186	.151			
				5		.187-UP	.182			

自锁螺母【LOCK NUTS】

产品型号分解 Part Number Designation




METRIC (公制)	尺寸单位: MM All Dimensions are in Millimeters										
	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	底端码 Shank Code	A (Shank) Max.	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C Max	E	T	最小边距 Min.Dist Hole
							+0.08				
	M3*0.5	SL	M3	1	0.98	1	4.25	4.22	6.3	1.5	4.8
				2	1.38	1.4					
	M3.5*0.6	SL	M3.5	1	0.98	1	4.75	4.73	7.1	1.5	5.6
				2	1.38	1.4					
	M4*0.7	SL	M4	1	0.98	1	5.4	5.38	7.9	2	6.9
				2	1.38	1.4					
	M5*0.8	SL	M5	1	0.98	1	6.4	6.38	8.7	2	7.1
				2	1.38	1.4					
	M6*1	SL	M6	1	1.38	1.4	8.75	8.72	11.05	4.08	8.6
				2	2.21	2.3					
	M8*1.25	SL	M8	1	1.38	1.4	10.5	10.47	12.7	5.47	9.7
				2	2.21	2.3					
	M10*1.5	SL	M10	1	2.21	2.29	14	13.97	17.35	7.48	13.5
				2	3.05	3.18					

INCHES (英制)	尺寸单位: 英寸 All Dimensions are in Inches										
	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	底端码 Shank Code	A (Shank) Max.	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C Max	E	T	最小边距 Min.Dist
							+0.08				
	.112-40 (#4-40)	SL	440	1	.038	.040	.166	.165	.250	.070	.19
				2	.054	.056					
	.138-32 (#6-32)	SL	632	1	.038	.040	.1875	.187	.280	.070	.22
				2	.054	.056					
	.164-32 (#8-32)	SL	832	1	.038	.040	.213	.212	.310	.090	.27
				2	.054	.056					
	.190-32 (#10-32)	SL	032	1	.038	.040	.250	.249	.340	.090	.28
				2	.054	.056					
	.250-20 (1/4-20)	SL	0420	1	.054	.056	.344	.343	.440	.170	.34
				2	.087	.091					
	.313-18 (5/16-18)	SL	0518	1	.054	.056	.413	.412	.500	.230	.38
				2	.087	.091					

防松自锁螺母【SELF LOCKING NUTS】

产品型号分解 Part Number Designation

PLC - M3
↓ ↓
Type and Thread
Material Cold




METRIC (公制)	尺寸单位: MM All Dimensions are in Millimeters												
	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	A (Shank) Max.	板厚 Sheet Thickness	安装孔 Hole Size In Sheet	C Max	D Max	E Max	T Max	最小边距 Min.Dist. Hole C/L To Edge	连接零件 上的孔
		钢 steel	不锈钢 Stainless Steel				0.08						
	M3*0.5	PL	PLC	M3	1.52	1.5-1.78	6	5.97	5.5	7.1	3.6	4.3	3.5
	M4*0.7	PL	PLC	M4	1.52	1.5-1.78	7.5	7.47	7	8.6	4.2	5.6	4.5
	M5*0.8	PL	PLC	M5	1.52	1.5-1.78	8	7.97	7.5	8.9	4.5	6.4	5.5

UNIFIED(英制)	尺寸单位: 英寸 All Dimensions are in Inches												
	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	A (Shank) Max.	板厚 Sheet Thickness	安装孔 Hole Size In Sheet	C Max	D Max	E Max	T Max	最小边距 Min.Dist. Hole C/L To Edge	连接零件 上的孔
		钢 steel	不锈钢 Stainless Steel				0.08						
	.112-40 (#4-40)	PL	PLC	440	.060	.059-.070	.234	.233	.216	.28	.130	.17	.132
	.138-32 (#8-32)	PL	PLC	632	.060	.059-.070	.265	.264	.246	.31	.130	.19	.158
	.164-32 (#6-32)	PL	PLC	832	.060	.059-.070	.297	.296	.279	.34	.155	.22	.184
	.190-32 (#10-32)	PL	PLC	032	.060	.059-.070	.312	.311	.292	.35	.165	.25	.210

微型螺母【SELF LOCKING NUTS】

产品型号分解 Part Number Designation

FE - M3 - 1 EF
 UL - 256 - CW
 ↓ ↓ ↓ ↓
 Type Thread Shank Finish
 Code Code Code Code



尺寸单位: MM
All Dimensions are in Millimeters

	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	低端码 Shank Code	板厚 Sheet Thickness	安装孔 Hole Size In Sheet	A (Shank) MAX	C -0.13	D MAX	E $\pm$ 0.13	T +0.4	重量 Weight LBS./K	最小边距 Min. Dist Hole C/L To Edge	安装后最大 接触孔 Max. Hole in Attached
		非自锁 Non Locking	自锁 Self Locking												
METRIC (公制)	M2*0.4	U	UL	M2	1	0.76-0.91	3.61	0.76	3.6	2.5	4.07	1.65	0.08	2.8	2.5
	M3*0.5	FE0X	FEO	M3	(4)	0.99-1.14	4.39	1.02	4.37	###	4.88	1.9	0.13	3.6	3.5
		FEX	FE			1.5-1.78		1.53					0.17		
	M4*0.7	FE0X	FEO	M4	(4)	0.99-1.14	7.39	1.02	7.37	###	8.17	2.55	0.5	5.2	4.5
		FEX	FE			1.5-1.78		1.53					0.54		
	M5*0.8	FE0X	FEO	M5	(4)	0.99-1.14	7.39	1.02	7.37	###	8.17	3.05	0.55	5.2	5.5
		FEX	FE			1.5-1.78		1.53					0.59		
	M6*1	FEX	FE	M6	(4)	1.5-1.78	8.74	1.53	8.72	###	9.74	3.3	0.95	7.1	6.5


尺寸单位: 英寸
All Dimensions are in Inches

	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	低端码 Shank Code	板厚 Sheet Thickness	安装孔 Hole Size In Sheet	A (Shank) MAX	C -0.005	D MAX	E $\pm$ 0.005	T +0.015	重量 Weight LBS./K	最小边距 Min. Dist Hole C/L To Edge	安装后最大 接触孔 Max. Hole in Attached
		非自锁 Non Locking	自锁 Self Locking												
UNIFIED (英制)	.060-80 (#0-80)	U	UL	080	0	.019-.022	.110	.020	.1095	###	.125	.050	.068	.09	.080
	.073-64 (#1-64)	U	UL	164	0	.019-.022	.110	.020	.1095	###	.125	.050	.070	.09	.093
	.086-56 (#2-56)	U	UL	256	0	.019-.022	.144	.020	.1435	###	.160	.065	.125	.11	.106
					1	.030-.036		.031					.184		
	.112-40 (#4-40)	FE0X	FEO	440	(4)	.039-.045	.172	.040	.171	###	.192	.065	.31	.14	.132
		FEX	FE			.059-.070		.060					.37		
	.138-32 (#6-32)	FE0X	FEO	632	(4)	.039-.045	.213	.040	.212	###	.244	.075	.47	.17	.158
		FEX	FE			.059-.070		.060					.68		
	.164-32 (#8-32)	FE0X	FEO	832	(4)	.039-.045	.290	.040	.289	###	.322	.090	.98	.20	.184
		FEX	FE			.059-.070		.060					1.24		
	.190-32 (#10-32)	FE0X	FEO	032	(4)	.039-.045	.290	.040	.089	###	.322	.110	1.04	.20	.210
		FEX	FE			.059-.070		.060					1.2		
	1/4-20 1/4-28	FEX	FE	0420	(4)	.059-.070	.344	.060	.343	###	.384	.120	2.08	.28	.270
				0428									1.58		

压铆螺钉【SELF CLINCHING STUD】

产品型号分解 Part Number Designation



FH - M3 - 6 ZI
 ↓ ↓ ↓ ↓
 Type Thread Length Finish
 Code Code



尺寸单位: MM All Dimensions are in Millimeters												
METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE			螺纹码 Thread Code	长度码 Length Code "L" ±0.4	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08 -0.00	安装后最大 接触孔 Max. Hole in Attach Parts	H ±0.4	S Max	最小边距 Min. Dist Hole C/L To Edge
		钢 Steel	不锈钢 Stainless Steel	铝 Aluminum								
	M2.5*0.45	FH	FHS	FHA	M2.5	4 6 8 10 12 15 18 20	1	2.5	3.1	4.1	1.95	5.4
	M3*0.5	FH	FHS	FHA	M3		1	3	3.6	4.6	2.1	5.6
	M3.5*0.6	FH	FHS	FHA	M3.5		1	3.5	4.1	5.3	2.25	6.4
	M4*0.7	FH	FHS	FHA	M4		1	4	4.6	5.9	2.4	7.2
	M5*0.8	FH	FHS	FHA	M5		1	5	5.6	6.5	2.7	7.2
	M6*1	FH	FHS	FHA	M6		1.6	6	6.6	8.2	3	7.9
	M8*1.25	FH	FHS	FHA	M8		2.4	8	8.6	9.6	3.7	9.6
尺寸单位: 英寸 All Dimensions are in Inches												
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE			螺纹码 Thread Code	长度码 Length Code "L" ±.015	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +.003 -.000	安装后最大 接触孔 Max. Hole in Attach Parts	H ±.015	S Max	最小边距 Min. Dist Hole C/L To Edge
		钢 Steel	不锈钢 Stainless Steel	铝 Aluminum								
	.086-56 (#2-56)	FH	FHS	FHA	256	4 6 8 10 12 15 18 20 25 30	.040	.085	.105	.144	.075	.187
	.112-40 (#4-40)	FH	FHS	FHA	440		.040	.111	.135	.176	.085	.219
	.138-32 (#6-32)	FH	FHS	FHA	632		.040	.137	.160	.206	.090	.250
	.164-32 (#8-32)	FH	FHS	FHA	832		.040	.163	.185	.237	.090	.281
	.190-24 (#10-24)	FH	FHS	FHA	024		.040	.189	.210	.256	.100	.281
	.190-32 (#10-32)	FH	FHS	FHA	032		.040	.189	.210	.256	.100	.281
	.250-20 (1/4-20)	FH	FHS	FHA	0420		.062	.249	.270	.337	.135	.312
	.313-18 (5/16-18)	FH	FHS	FHA	0518		.093	.311	.333	.376	.160	.375

压铆螺钉【SELF CLINCHING STUD】

产品型号分解 Part Number Designation



尺寸单位：MM
All Dimensions are in Millimeters



METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度码 Length Code*L*±0.4									最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet +0.08 -0.00	H ±0.4	S MAX.	最小边距 Min.Dist Hole C/L To Edge
		不锈钢 Stainless Steel															
	M3*0.5	FH4	M3	6	8	10	12	15	18	20	25	NA	1-2.4	3	4.6	2.1	5.6
	M4*0.7	FH4	M4	6	8	10	12	15	18	20	25	30	1-2.4	4	5.9	2.4	7.2
	M5*0.8	FH4	M5	NA	8	10	12	15	18	20	25	30	1-2.4	5	6.5	2.7	7.2
	M6*1	FH4	M6	NA	NA	10	12	15	18	20	25	30	1.6-3	6	8.2	3	7.9

尺寸单位：英寸
All Dimensions are in Inches

UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度码 Length Code*L*±.015									最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet +.003 -.000	H ±.015	S MAX.	最小边距 Min.Dist Hole C/L To Edge
		不锈钢 Stainless Steel		.250	.312	0.375	.500	.625	.750	.875	1.00	1.25					
	.112-40 (#4-40)	FH4	440	4	5	6	8	10	12	14	NA	NA	.040~.095	.111	.176	.085	.219
	.138-32 (#6-32)	FH4	632	4	5	6	8	10	12	14	16	20	.040~.095	.137	.206	.090	.250
	.164-32 (#8-32)	FH4	832	4	5	6	8	10	12	14	16	20	.040~.095	.163	.237	.090	.281
	.190-32 (#10-32)	FH4	032	NA	5	6	8	10	12	14	16	20	.040~.095	.189	.256	.090	.281
	.250-20 (1/4-20)	FH4	0420	NA	NA	6	8	10	12	14	16	20	.062~.117	.249	.337	.135	.312

压铆销钉【FLUSH HEAD PINS】

产品型号分解 Part Number Designation



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	直径 Nominal Pin Diameter P ±0.05	型号 TYPE			长度码 Length Code "L" ±0.4										最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08 -0.00	H ±0.4	S MAX.	最小边 距 Min. Dist Hole C/L To Edge
		钢 Steel	不锈 锈钢 Stainless	铝 Aluminum	销钉 直径 代码	6	8	10	12	15	18	20	25	30					
	3	FH	FHS	FHA	3MM										1	3.5	5.3	2.3	6.4
	4	FH	FHS	FHA	4MM	NA									1	4.1	6	2.3	7.1
	5	FH	FHS	FHA	5MM	NA									1	5.5	7.5	2.55	7.6

尺寸单位: 英寸

All Dimensions are in Inches

UNIFIED (英制)	直径 Nominal Pin Diameter P ±0.05	型号 TYPE			销钉 直径代 码	长度码 Length Code "L" ±.015								最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet + .003 - .000	H ±.015	S MAX.	最小边 距 Min. Dist Hole C/L To Edge	
		钢 Steel	不锈 钢 Stainless Steel	铝 Alum inum		.250	.312	0.375	.500	.625	.750	.875	1.00						1.25
	.073	FH	FHS	FHA	073	4	5	6	8	10	NA	NA	NA	NA	.040	.085	.15	.075	.19
	.084	FH	FHS	FHA	084	4	5	6	8	10	12	NA	NA	NA	.040	.099	.16	.085	.22
	.094	FH	FHS	FHA	094	4	5	6	8	10	12	NA	NA	NA	.040	.111	.18	.085	.22
	.103	FH	FHS	FHA	103	4	5	6	8	10	12	NA	NA	NA	.040	.118	.18	.085	.22
	.106	FH	FHS	FHA	106	4	5	6	8	10	12	14	16	20	.040	.125	.19	.090	.22
	.116	FH	FHS	FHA	116	4	5	6	8	10	12	14	16	20	.040	.137	.21	.090	.25
	.120	FH	FHS	FHA	120	4	5	6	8	10	12	14	16	20	.040	.137	.21	.090	.25
	.137	FH	FHS	FHA	137	4	5	6	8	10	12	14	16	20	.040	.157	.23	.090	.28
	.141	FH	FHS	FHA	141	4	5	6	8	10	12	14	16	20	.040	.163	.24	.090	.28
	.160	FH	FHS	FHA	160	4	5	6	8	10	12	14	16	20	.040	.189	.26	.100	.28
	.167	FH	FHS	FHA	167	NA	5	6	8	10	12	14	16	20	.040	.189	.26	.100	.28
	.173	FH	FHS	FHA	173	NA	5	6	8	10	12	14	16	20	.040	.197	.26	.100	.28
	.207	FH	FHS	FHA	207	NA	5	6	8	10	12	14	16	20	.062	.236	.32	.135	.31
	.215	FH	FHS	FHA	215	NA	NA	NA	8	10	12	14	16	20	.062	.250	.34	.135	.31
	.223	FH	FHS	FHA	223	NA	NA	NA	8	10	12	14	16	20	.062	.250	.34	.135	.31
	.273	FH	FHS	FHA	273	NA	NA	NA	8	10	12	14	16	20	.093	.312	.38	.160	.38
	.281	FH	FHS	FHA	281	NA	NA	NA	8	10	12	14	16	20	.093	.312	.38	.160	.38

非平头压铆螺钉 【NON FLUSH SELF CLINCHING STUDS】


产品型号分解 Part Number Designation

TFH - M3 - 8

↓ ↓ ↓

Type Thread Length

Code Code Code



尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	长度码 Length Code "L"	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件 上的孔	H ±0.4	S max	T max
		钢 Steel	不锈钢 Stainless Steel		±0.4						
	M3*0.5	TFH	TFHS	M3	6-35	0.51	3	3.3	4.5	1.8	0.64
	M4*0.7			M4		0.51	4	4.7	5.8	1.8	0.64
	M5*0.8			M5		0.51	5	5.3	6.4	2.3	0.64

尺寸单位: 英寸 All Dimensions are in Inches											
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	长度码 Length Code "L"	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件 上的孔	H ±.015	S max	T max
		钢 Steel	不锈钢 Stainless Steel		±.015						
	.086-56 (#2-56)	TFH	TFHS	256	4-24	.020	.085	.105	.141	.070	.025
	.112-40 (#4-40)			440		.020	.111	.135	.176	.070	.025
	.138-32 (#6-32)			632		.020	.137	.160	.203	.070	.025
	.164-32 (#8-32)			832		.020	.163	.185	.234	.070	.025
	.190-24 (#10-24)			024		.020	.189	.210	.250	.090	.025
	.190-32 (#10-32)			032		.020	.189	.210	.250	.090	.025

小头窄型压铆螺钉【SELF CLINCHING STUD】



产品型号分解 Part Number Designation

FHL - M3 - 8

↓ ↓ ↓

Type Thread Length

Code Code Code



尺寸单位: MM All Dimensions are in Millimeters										
METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	长度代码"L"单位mm	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件上的孔	H ±0.4	S max
		钢 Steel	不锈钢 Stainless Steel		±0.4					
	M2.5*0.45	FHL	FHLS	M2.5	6-35	1	2.5	2.9	3.15	2.1
	M3*0.5			M3		1	3	3.4	3.65	2.1
	M3.5*0.6			M3.5		1	3.5	3.9	4.15	2.3
	M4*0.7			M4		1	4	4.4	4.65	2.4
	M5*0.8			M5		1	5	5.4	5.9	2.7
尺寸单位: 英寸 All Dimensions are in Inches										
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	长度代码"L"单位 Length Code "L"	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件上的孔	H ±.015	S max
		钢 Steel	不锈钢 Stainless Steel		±.015					
	.086-.56 (#2-.56)	FHL	FHLS	256	4-24	.040	.085	.100	.112	.080
	.112-.40 (#4-.40)			440		.040	.111	.125	.138	.085
	.138-.32 (#6-.32)			632		.040	.137	.150	.164	.090
	.164-.32 (#8-.32)			832		.040	.163	.180	.190	.090
	.190-.32 (#10-.32)			032		.040	.189	.205	.225	.100

重载压铆螺钉【HIGH STRENGTH CLINCHING STUDS】



产品型号分解 Part Number Designation

HFH - M5 - 10

↓ ↓ ↓

Type Thread Length

Code Code Code




尺寸单位: MM All Dimensions are in Millimeters												
METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE			螺纹码 Thread Code	长度代码"L"单位mm Length Code"L"	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	连接零件上的孔	H ±0.25	S max	T max
		钢 Steel	不锈钢 Stainless Steel			±0.4						
	M5*0.8	HFH	HFHS	HFHB	M5	15-50	1.3	5	6.4	7.8	2.7	1.14
	M6*0.1				M6		1.5	6	7.5	9.4	2.8	1.27
	M8*1.25				M8		2	8	9.5	12.5	3.5	1.78
	M10*1.5				M10		2.3	10	11.5	15.7	4.1	2.29
尺寸单位: 英寸 All Dimensions are in Inches												
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE			螺纹码 Thread Code	长度代码"L"单位in Length Code"L"	板厚厚度 Min.Sheet Thickness	安装孔 Hole Size In Sheet	连接零件上的孔	H ±.015	S max	T
		钢 Steel	不锈钢 Stainless Steel	铜 Brass		±.015						
	.190-32 (#10-32)	HFH	HFHS	HFHB	032	.500-2	.050	.190	.252	.300	.105	.040
	.250-20 (1/4-20)				0420		.060	.250	.312	.380	.125	.050
	.313-18 (5/16-18)				0518		.075	.312	.374	.480	.140	.070
	.375-16 (3/8-16)				0616		.090	.375	.437	.580	.155	.085

薄板重载螺钉【HEAVY DUTY SELF CLINCHING STUDS】

产品型号分解Part Number Designation

HFE - M5 - 10

Type Thread Cold Length Code



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度代码"L"单位mm Length Code "L"	板厚厚度 Min. Sheet Thickness	安装孔 Hole Size In Sheet	安装后最大 接触孔 Max. Hole in Attach Parts	H ±0.25	S max	T max
				±0.4		+0.13				
	M5*0.8	HFE	M5	15-50	1	5	7.3	9.6	2.6	1.35
	M6*0.1		M6		1	6	8.3	11.35	2.8	1.52
M8*1.25	M8		1.5		8	10.3	15.3	3.3	2.13	

尺寸单位: 英寸

All Dimensions are in Inches


UNITED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度代码"L"单位in Length Code "L"	板厚厚度 Min. Sheet Thickness	安装孔 Hole Size In Sheet	安装后最大 接触孔 Max. Hole in Attach Parts	H ±.01	S max	T max
				±.015		+.005 -.000				
	.190-32 (#10-32)	HFE	032	.500-2	.040	.190	.280	.357	.102	.048
	.250-20 (1/4-20)		0420		.040	.250	.340	.462	.118	.060
.313-18 (5/16-18)	0518		.060		.312	.402	.586	.133	.083	

挤压螺钉【SELF CLINCHING STUD】

产品型号分解Part Number Designation

KFH - M3 - 8

Type Thread Cold Length Code



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度代码"L"单位mm Length Code "L"	A (Shank) Max.	板厚厚度 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件 上的孔	H ±0.25	S max	T ±0.13
				+0.08							
	M3*0.5	KFH	M3	6-18	1.65	1.53	3	3.7	4.58	2.3	0.51
	M4*0.7		M4		1.65	1.53	4.2	4.8	5.74	2.3	0.51
	M5*0.8		M5		1.65	1.53	5	5.8	6.6	2.3	0.51



尺寸单位: 英寸

All Dimensions are in Inches

UNITED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	长度代码"L"单位in Length Code "L"	A (Shank) Max.	板厚厚度 Min. Sheet Thickness	安装孔 Hole Size In Sheet	连接零件 上的孔	H ±.01	S max	T ±0.13
				±.015							
	.112-40 (#4-40)	KFH	440	.250-.750	.065	.060	.120	.145	.180	.090	.020
	.138-32 (#6-32)		632		.065	.060	.140	.170	.200	.090	.020
	.164-32 (#8-32)		832		.065	.060	.166	.195	.225	.090	.020
.190-32 (#10-32)	032		.065		.060	.189	.220	.250	.090	.020	

焊接螺钉【WELD STUDS】

产品型号分解Part Number Designation





尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	型号 TYPE		螺纹码 Thread Code	长度码 Length Code “L”mm	dk		dp		Z		k	
	不锈钢 Stainless Steel	镀铜 Steel Copper Yellow			max	min	max	min	max	min	max	min
	FES	FE	M3	6 8 10 12 15 20 .	4.65	4.35	0.78	0.52	0.53	0.27	1.3	0.7
	FES	FE	M4		5.65	5.35	0.78	0.52	0.63	0.37	1.3	0.7
	FES	FE	M5		6.68	6.32	0.88	0.62	0.73	0.47	1.4	0.8
	FES	FE	M6		7.68	7.32	0.88	0.62	0.83	0.57	1.4	0.8
	FES	FE	M8		9.72	9.29	0.88	0.62	0.93	0.67	1.5	0.9
	FES	FE	M10		11.72	11.29	1.1	0.85	1.03	0.77	1.5	0.9
	FES	FE	M12		14.22	13.79	1.1	0.85	1.13	0.87	1.5	0.9

六角螺钉【HEXAGON SELF CLINCHING STUDS】

产品型号分解Part Number Designation



尺寸单位: MM
All Dimensions are in Millimeters

螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE		螺纹码 Thread Code	长度码 Length Code "L"mm	最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	H	S	最小边距 Min.Dist. Hole C/L To Edge
	碳钢 Carbon Steel	不锈钢 Stainless Steel				±0.08	±0.15	MAX	
M3*0.5	NFH	NFHS	M3	6 8 10 12 15 20 .	1	4.8	6.0	1.25	5.6
M4*0.7	NFH	NFHS	M4		1	5	6.0	1.25	7.2
M5*0.8	NFH	NFHS	M5		1	5	6.35	1.25	7.2
M6*1.0	NFH	NFHS	M6		1.3	6.0	7.0	1.40	7.9

埋头螺钉【CONCEALED-HEAD STUD】




产品型号分解 Part Number Designation

CHC - M3 - 6

↓ ↓ ↓

Type Thread Length

Code Code Code



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE		螺纹码 Thread Code	长度码 Length Code "L" mm	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	最小安装 孔深 MinDepth of Blind Hole	A	E	C	最小边距 Min. Dist Hole C/L To Edge	安装后最 大接触孔 Max. Hol In Attache Parts
		铝 Aluminum	不锈钢 Stainless Steel						MAX.	±0.25	MAX.		
	M3*0.5	CHA	CHC	M3	6 8 10 12 16 20	1.6	4.37	1.1	1.04	5.21	4.35	4	3.5
		CFHA	CFHC			2.4		1.91	1.8				
	M4*0.7	CHA	CHC	M4		1.6	7.37	1.1	1.04	8.33	7.35	5.5	4.6
		CFHA	CFHC			2.4		1.91	1.8				
	M5*0.8	CHA	CHC	M5		1.6	7.39	1.1	1.04	8.89	7.9	6.4	5.6
		CFHA	CFHC			2.4		1.91	1.8				

尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED (英制)	螺 纹 尺 寸*螺 距 Thread Size*Pitch	型 号 TYPE		螺 纹 码 Thread Code	长 度 码 Length Code “L”	最 小 板 厚 Min. Sheet Thickness	安 装 孔 Hole Size In Sheet	最 小 安 装 孔 深 MinDepth of Blind Hole	A	E	C	最 小 边 距 Min. Dist Hole C/L To Edge	安 装 后 最 大 接 触 孔 Max. Hole In Attache Parts
		铝 Aluminum	不 锈 钢 Stainless Steel						MAX	±.010	MAX		
	.112-40 (#4-40)	CHA	CHC	440		.062	.172	.043	.041	.205	.171	.156	.135
		CFHA	CFHC			.093		.075	.071				
	.138-32 (#6-32)	CHA	CHC	632		.062	.213	.043	.041	.250	.212	.188	.160
		CFHA	CFHC			.093		.075	.071				
	.164-32 (#8-32)	CHA	CHC	832		.062	.290	.043	.041	.328	.289	.219	.185
		CFHA	CFHC			.093		.075	.071				
	.190-32 (#10-32)	CHA	CHC	032		.062	.312	.043	.041	.350	.311	.250	.210
		CFHA	CFHC			.093		.075	.071				

盲孔压铆螺柱【SELF CLINCHING STANDOFFS】


产品型号分解Part Number Designation

BSO - M3 - 6

↓ ↓ ↓

Type Thread Length

Code Code Code



尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE				螺纹码 Thread Code	长度码 Length Code*L*mm +0.05-0.13																			最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C -0.13	H Nom	最小边距 Min. Dist																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron	铝 Aluminum																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															


尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED(英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE				螺纹码 Thread Code	长度码 Length Code"L*mm +.002-.005																最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C -.005	H Nom	最小边距 Min. Dist
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron	铝 Aluminu m		.125	.187	.250	.312	.375	.437	.500	.562	.625	.687	.750	.812	.875								
	.112-40 (#4-40)	BSO	BSOS	BSO4	BSOA	440	4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6			
	6440																										
	632					4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6				
	8632																										
	832					4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6				
	.190-32 (#10-32)					032	4	6	8	10	12	14	16	18	20	22	24	26	28	1	5.4	5.38	6.35	6.8			

通孔孔压铆螺柱【SELF CLINCHING STANDOFFS】

产品型号分解Part Number Designation

SO - M3 - 6
 ↓ ↓ ↓
 Type Thread Length
 Code Code



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺 距 Thread Size*Pitch	型号 TYPE				螺纹码 Thread Code	长度码 Length Code*L*mm +0.05-0.13																			最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	最小边距 Min.Dist. Hole C/L To Edge		
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron	铝 Aluminu m		C -0.13	H Nom																						
	M2*0.4	SO	SOS	SO4	SOA	M2	3	4	5	6	8	10	12	14	15	16	18	20	25	1	4.2	4.19	4.75	6						
	M2.5*0.45					M2.5	3	4	5	6	8	10	12	14	15	16	18	20	25	1	4.2	4.19	4.75	6						
	M3*0.5					M3	3	4	5	6	8	10	12	14	15	16	18	20	25	1	4.2	4.19	4.75	6						
	3.5M3*0.5					3.5M3	3	4	5	6	8	10	12	14	15	16	18	20	25	1	5.4	5.38	6.35	6.8						
	M3.5*0.6					M3.5	3	4	5	6	8	10	12	14	15	16	18	20	25	1	5.4	5.38	6.35	8.8						
	M4*0.7					M4	3	4	5	6	8	10	12	14	15	16	18	20	25	1.3	6	5.98	7	8						
	3.5M4*0.7					3.5M4	3	4	5	6	8	10	12	14	15	16	18	20	25	1.3	7.2	7.15	8	8						
	M5*0.8					M5	3	4	5	6	8	10	12	14	15	16	18	20	25	1.3	7.2	7.15	8	8						
	M6*1.0					M6	3	4	5	6	8	10	12	14	15	16	18	20	25	1.3	8.8	8.75	10	10						
	M8*1.25					M8	3	4	5	6	8	10	12	14	15	16	18	20	25	1.3	11	10.95	13	14						

尺寸单位: 英寸

All Dimensions are in Inches

UNIFIED(英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE				螺纹码 Thread Code	长度码 Length Code"L"mm +.002-.005																最小板厚 Min.Sheet Thickness	安装孔 Hole Size In Sheet	C -.005	H Nom	最小边距 Min.Dist. Hole C/L To Edge
		碳钢 Carbon Steel	不锈钢 Stainless Steel	不锈钢 Stainless Iron	铝 Aluminum		.125	.187	.250	.312	.375	.437	.500	.562	.625	.687	.750	.812	.875								
	.112-40 (#4-40)	SO	SOS	SO4	SOA	440	4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6			
	6440					4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6				
	.138-32 (#6-32)					632	4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6			
	8632					4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6				
	.164-32 (#8-32)	832	4	6	8	10	12	14	16	18	20	22	24	26	28	1	4.2	4.19	4.75	6							
	.190-32 (#10-32)	32	4	6	8	10	12	14	16	18	20	22	24	26	28	1	5.4	5.38	6.35	6.8							

花齿压铆螺柱【SELF CLINCHING STANDOFFS】


产品型号分解Part Number Designation

DSOS - M3 - 7

↓ ↓ ↓

Type Thread Length

Code Code Code



尺寸单位: MM

All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	类型 TYPE		螺纹码 Thread Code	长度码 Length Code "L" mm +0.05-0.13	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	C MAX	H NOM	最小边距 Min. Dist. Hole C/L To Edge
		不锈钢 Stainless Steel	碳钢 Carbon Steel				+0.08			
	M3*0.5	DSOS	DS0	M3	6.35	0.94-6.35	4.2	4.2	4.92	3.2
					7					

尺寸单位: 英寸

All Dimensions are in Inches

UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	类型 TYPE		螺纹码 Thread Code	长度码 Length Code "L" mm +.002-.005	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet	C MAX	H NOM	最小边距 Min. Dist. Hole C/L To Edge
		不锈钢 Stainless Steel	碳钢 Carbon Steel				+0.08			
	.112-40 (#4-40)	DSOS	DS0	440	250	.037-.025	.166	.165	.194	.126
					270					

无台阶防水螺母柱【BLIND STANDOFFS】


产品型号分解Part Number Designation

BSS - M6 - 10 - 1

↓ ↓ ↓ ↓

Type Thread Length Shank

Code Code Code Code



尺寸单位: MM


All Dimensions are in Millimeters

型号 TYPE	螺纹尺寸*螺距 Thread Size*Pitch	底端码 Shank Code	A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	E	L	T	H	最小边距 Min. Dist. Hole C/L To Edge
						max	±0.25	±0.25	±0.1	min	
BS S	M3*0.5	0	0.77	0.8-1	4.25	4.22	6.35	10	1.1	5.3	4.8
		1	0.97	1							
		2	1.38	1.4							
	M4*0.7	0	0.77	0.8-1	5.4	5.38	7.95	10	1.4	7.1	6.9
		1	0.97	1							
		2	1.38	1.4							
	M5*0.8	0	0.77	0.8-1	6.4	6.38	8.75	10	1.4	7.1	7.1
		1	0.97	1							
		2	1.38	1.4							
	M6*1.0	0	1.15	1.2	8.75	8.72	11.1	10	1.5	6.3	8.6
		1	1.38	1.4							
		2	2.21	2.3							
	M8*1.25	1	1.38	1.4	10.5	10.47	12.65	16	2	10	9.7
		2	2.21	2.3				20		14	
	M12*1.75	2	1.95	2	14.1	14.1	17	20	3	14	10.8
								30		24	

防水螺母柱【BLIND STANDOFFS】



产品型号分解 Part Number Designation

BS	-	M3	-	1
↓		↓		↓
Type		Thread Cold		Shank Code

[illegible][illegible]

种焊螺柱【WELD STANDOFFS】



产品型号分解Part Number Designation



尺寸单位：MM All Dimensions are in Millimeters									
螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE		螺纹码 Thread Code	长度码 Length Code “L”mm	焊点高度 weld Point High	焊点外径 weld Point Diameter	头部厚度 Head Thickness	头部外径 Head Diameter	螺柱外径 Diameter
	不锈钢 Stainless Steel	镀铜 Steel Copper Yellow			Z	DP	K	DK	D
M3*0.5	ITS	IT	M3	6 8 10 12 15	0.7	0.8	1	6.5	5
M4*0.7	ITS	IT	M4		0.7	0.8	1	7.5	6
M5*0.8	ITS	IT	M5		0.7	0.8	1	8.5	7
M6*1.0	ITS	IT	M6		0.7	1	1	9.5	8
M8*1.25	ITS	IT	M8		0.7	1	1	11.5	10

反盲孔压铆螺柱【ANTI BLIND HOLE STANDOFFS】

产品型号分解 Part Number Designation



尺寸单位：MM





All Dimensions are in Millimeters

METRIC (公制)	螺 纹 尺 寸*螺 距 Thread Size*Pitch	型 号 TYPE			螺 纹 码 Thread Code	最 小 板 厚 Min. Sheet Thickness	安 装 孔 Hole Size In Sheet	C -0.13	H	最 小 边 距 Min. Dist. Hole C/L To Edge
		碳 钢 Carbon Steel	不 锈 钢 Stainless Steel	铝 Aluminum						
	M3*0.5	TBSO	TBSOS	TBSOA	M3	1	4.2	4.19	4.75	6
	3.5M3*0.5				3.5M3	1	5.4	5.38	6.35	6.8
	M4*0.7				M4	1.3	6	5.98	7	8
	3.5M4*0.7				3.5M4	1.3	7.2	7.15	8	8
	M5*0.8				M5	1.3	7.2	7.15	8	8
	M6*1.0				M6	1.3	8.8	8.75	10	10

埋头螺柱【CONCEALED HEAD STANDOFFS】

产品型号分解Part Number Designation

CSOS	- M3	- 6
↓	↓	↓
Type	Thead Cold	Length Code



Metric (公制)

尺寸单位: MM All Dimensions are in Millimeters												
螺纹尺寸*螺距 Thread Size*Pitch	不锈钢 Stainless Steel	螺纹码 Thread Code	长度码 Length Code "L"mm	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	最小安装孔深 Min.Depth Of Blind Hole	螺纹深度 Depth Full Thread T	A MAX	B MAX	C MAX.	H NOM	最小边距 Min. Dist. Hole C/L To Edge
M3*0.5	CSS	M3	4 6 8 10 12 16 20	1.6	5.41	1.1	5	1.04	4.2	5.39	6.35	4.8
	CSOS			2.4		1.91		1.83				
M4*0.7	CSS	M4		1.6	7.92	1.1	6.5	1.04	6.23	7.9	8.74	6.4
	CSOS			2.4		1.91		1.83				
M5*0.8	CSS	M5		1.6	8.74	1.1	9.6	1.04	7.37	8.72	9.53	7.2
	CSOS			2.4		1.91		1.83				
M6*1	CSS	M6		2.4	9.9	1.91	9.6	1.83	1.83	9.89	11.11	9.5
	CSOS											

UNIFIED (英制)

尺寸单位: 英寸
All Dimensions are in Inches

螺纹尺寸*螺距 Thread Size*Pitch	不锈钢 Stainless Steel	螺纹码 Thread Code	长度码 Length Code "L"mm	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	最小安装孔深 Min.Def Of Blind Hole	螺纹深度 Depth Full Thread T	A MAX	B MAX	C MAX.	H NOM	最小边距 Min. Dist. Hole C/L To Edge
.112-40 (#4-40)	CSS	440	4 6 8 10 12 16 20 ...	.062	0.213	0.043	0.2	0.041	0.165	CSS	.250	0.188
	CSOS			0.093		0.075		.072				
.138-32 (#6-32)	CSS	632		0.062	0.29	0.043	0.25	0.041	0.213	.289	.312	0.218
	CSOS			0.093		0.075		0.072				
.164-32 (#8-32)	CSOS	832		0.062	.312	0.043	0.25	0.041	.245	.311	.344	0.25
				0.093		0.075		.072				
.343	CSS	32		62	0.344	0.043	.375	0.041	0.29	.343	.375	0.281
	CSOS			.093		.075		.072				
.250-20 (1/4-20)	CSS	0420		.062	.380	.043	.375	.041	.354	.389	.438	.375
	CSOS			.093		.075		.072				


支撑卡柱【SNAP TOP STANDOFFS】

产品型号分解Part Number Designation

SSS - 4mm - 8 ZU

↓ ↓ ↓ ↓

Type and Diameter Length Finish
Material Code code Code



尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	型号TYPE			安装孔 Hole Size In Sheet	长度编码“L”±0.13 Length Code“L” 长度(英寸)=长度编码/32	B	C	H	D
	铝 Aluminum	碳钢 Carbon Steel	不锈钢 Stainless Steel			±0.13	MAX	±0.13	±0.13
	SSA	SSS	SSC			4.78	5.39	6.35	3.58

尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED (英制)	型号TYPE			安装孔 Hole Size In Sheet	长度编码“L”±.005 Length Code“L” 长度(英寸)=长度编码/32	B	C	H	D
	铝 Aluminum	碳钢 Carbon Steel	不锈钢 Stainless Steel			±.005	MAX	±.005	±.005
	SSA	SSS	SSC			.188	.212	.250	.141


支撑卡柱【SNAP TOP STANDOFFS】

产品型号分解Part Number Designation

KSSB - 4MM - 8 X

↓ ↓ ↓ ↓

Type and Diameter Length Finish
Material Code code Code



尺寸单位: MM
All Dimensions are in Millimeters



METRIC (公制)	铜 Brass	安装孔 Hole Size In Sheet	长度编码 “L” ±0.13 Length Code “L” 长度(英寸)=长度编码/32	B	C	H	D	T
	KSSB	4mm		±0.13	MAX	±0.13	±0.13	±0.13
	KSSB	4mm		4.8	5.74	6.35	3.58	0.51

尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED (英制)	铜 Brass	安装孔 Hole Size In Sheet	长度编码 “L” ±.005 Length Code “L” 长度(英寸)=长度编码/32	B	C	H	D	T
	KSSB	156		±.005	MAX	±.005	±.005	±.005
	KSSB	156		.188	.226	.250	.141	.020

定位支撑柱【KEYHOLE STANDOFFS】

产品型号分解Part Number Designation





尺寸单位: MM All Dimensions are in Millimeters																	
METRIC (公制)	型号 TYPE	规格代号 Body Size- Sheet Code	安装孔 Hole Size In Sheet +0.08	长度编码 "L" ±0.13长度(毫米)=长度编码/32 Length Code "L"													A
																	B
	SKC	61.5	5.5	2	4	6	8	10	12	14	16	18	20	22	25	±0.08	±0.08
																MAX	±0.08
																MAX	MAX

UNIFIED(英制)	型号 TYPE	规格代号 Body Size- Sheet Code	安装孔 Hole Size In Sheet D +.003 -.000	长度编码 "L" ±.005长度(英寸)=长度编码/32 Length Code "L"													A
																	B
	SKC	6060	.216	.063	.125	.188	.250	.312	.312	.375	.500	.562	.625	.750	.875	±.003	±.005
																MAX	±.003
																MAX	MAX

压铆定位销【PILOT PINS】

产品型号分解Part Number Designation





尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	型号 TYPE	销钉直径 Diameter Code	长度码 Length Code					安装孔 Hole Size In Sheet +0.08	最小板厚 Min. Sheet Thickness	D±0.15	H±0.4	S Max	最小边距 Min. Dist. Hole C/L To Edge
	TPS	3mm	8	10	12	16	NA	3.5	1	2.05	5.2	2.29	6.4
	TPS	4mm	8	10	12	16	NA	4.5	1	2.82	6.12	2.29	7.1
	TPS	5mm	NA	10	12	16	20	5.5	1	3.53	7.19	2.29	7.6
	TPS	6mm	NA	NA	12	16	20	6.5	1	4.24	8.13	2.29	7.9

尺寸单位: 英寸 All Dimensions are in Inches													
UNIFIED(英制)	型号 TYPE	销钉直径 Diameter Code	长度码 Length Code					安装孔 Hole Size In Sheet +.003	最小板厚 Min. Sheet Thickness	D±.006	H±.015	S Max	最小边距 Min.Dist Hole C/L To Edge
			.375	.500	.625	.750	###						
	TPS	.125	6	8	10	12	NA	.144	.040	.090	.205	.090	.250
	TPS	.187	6	8	10	12	16	.205	.040	.132	.270	.090	.280
	TPS	.250	NA	8	10	12	16	.727	.040	.177	.335	.090	.310

微型定位销【PILOT PINS】

产品型号分解Part Number Designation



尺寸单位: MM


All Dimensions are in Millimeters

型号 TYPE	销直径 Diameter Code ±0.038	长度编码"L"±.005 Length Code							最小板厚 Min. Sheet Thickness		安装孔 Hole Size In Sheet		D		H		最小边距 Min. Dist. Hole C/L To Edge	
									mm	in	+0.025mm	+ .00lin	±0.1mm	±.004in	±0.25mm	±.010in	mm	in
MPP	1MM	2	3	4	5	NA	NA	NA	0.5	.020	1.05	.041	0.7	.028	1.6	.063	2.05	.081
	1.5MM	NA	3	4	5	6	8	NA	0.5	.020	1.55	.061	1.03	.041	2.24	.088	2.6	###
	2MM	NA	NA	4	5	6	8	10	0.5	.020	2.05	.081	1.36	.054	3.02	.119	4.4	###

PF09/PF10 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PF09 - M3 - 1 - NA
↓ ↓ ↓ ↓
Type and Thread Shank Finish
Material Code code




尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A (Shank) Max.	最小-最大 板厚 Min.sheet Thickness Min~Max	安装孔 Hole Size In Sheet +0.08	C	B	G	T1	T2	E	槽型尺寸 Driver Size
		铝 Aluminum	不锈钢 Stainless Steel						Max	±0.1	±0.4	Max	Max	±0.25	
	M2.5*0.45	PF09	PF10	M2.5	0	1	0.8-1.5	4	3.98	0.4	5.0	14.5	13.4	7	#1
					1	1.5	1.5-2.0	4	3.98	0.4	6.0	15.5			
					2	2.5	2.0-3.0	4	3.98	0.4	7.0	16.5			
	M3*0.5	PF09	PF10	M3	0	1	0.8-1.5	4.5	4.48	0.4	5.3	14.8	13.4	8	#1
					1	1.5	1.5-2.0	4.5	4.48	0.4	6.3	15.8			
					2	2.5	2.0-3.0	4.5	4.48	0.8	7.3	16.8			

PF11MW/PF12MW 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation



METRIC (公制)

尺寸单位: MM All Dimensions are in Millimeters																
螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	螺丝长度 Screw Length Code	A Max. sheet Thickness	B Min.	D安装孔 Hole Size In Sheet +0.08 -0.03	E ±0.25	G Nom.	H Min.	L1 Nom.	L2 Max	T1 Nom.	T2 Nom.	槽型尺寸 Driver Size	W Nom.
	滚花帽 Knurled Cap	光面帽 Smooth Cap														
M3*0.5	PF11MW	PF12MW	M3	1	1.6	2.82	6.35	10.59	5.84	9.52	3.48	3.23	7.87	11.43	#1	7.92
				2					7.37							
M3.5*0.6	PF11MW	PF12MW	M3.5	1	1.6	2.92	7.19	11.43	7.37	10.49	3.78	3.23	11.43	16.26	#2	8.74
				2					8.89							
M4*0.7	PF11MW	PF12MF	M4	1	1.6	3.07	8.79	13.06	7.37	11.91	3.99	3.56	11.43	16.26	#2	10.34
				2					8.89							
M5*0.8	PF11MW	PF12MF	M5	1	1.6	3.07	8.79	13.06	7.37	11.91	3.99	3.56	11.43	16.26	#2	10.34
				2					8.89							
M6*1	PF11MW	PF12MF	M6	1	1.6	3.25	10.49	14.61	8.89	13.48	3.99	3.56	13.46	20.07	#3	11.89
				2					10.41							


尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED(英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	螺丝长度 Screw Length Code	A Max. sheet Thicknes s	B Min.	D安装孔 Hole Size In Sheet +0.08 -0.03	E ±0.25	G Nom.	H Min.	L1 Nom.	L2 Max	T1 Nom.	T2 Nom.	槽型尺寸 Driver Size	W Nom.
		浪花帽 Knurled Cap	光面帽 Smooth Cap														
	.112-40 (#4-40)	PF11MW	PF12M W	440	1	.063	.111	.250	.417	.230	.375	.137	.127	.310	.450	#1	.312
					2					.219							
	.138-32 (#6-32)	PF11MW	PF12M W	632	1	.063	.115	.293	.450	.290	.413	.149	.127	.450	.640	#2	.344
					2					.350							
	.164.32 (#8-32)	PF11MW	PF12MF	832	1	.063	.121	.346	.514	.290	.469	.157	.140	.450	.640	#2	.407
					2					.350							
	.190.32 (#10-32)	PF11MW	PF12MF	032	1	.063	.121	.346	.514	.290	.469	.157	.140	.450	.640	#2	.407
					2					.350							
	.250-20 (#1/4-20)	PF11MW	PF12MF	0420	1	.063	.128	.413	.575	.350	.531	.157	.140	.450	.790	#3	.468
					2					.410							

PF15/PF41 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PF15 - M3 - 1 - BL
 ↓ ↓ ↓ ↓
 Type Thread Code Screw Length code Optional DuraBlack Finish



尺寸单位: MM
 All Dimensions are in Millimeters

螺纹尺寸*螺距 Thread Size*Pitch		型号 TYPE	螺纹码 Thread Code		安装孔 Hole Size In Sheet +0.08	板厚 Min. sheet Thickness Min`Max	A ±0.1	B ±0.1	C Max.	底端码 Shank Code	G ±0.4	T1 ±0.2	T2 Nom.	E ±0.25
METRIC（公制）	UNIFIED(英制)		METRIC（公制）	UNIFIED(英制)										
M3*0.5	.112~40 (#4~40)	PF15 PF41	M3	440	4.75	0.8~1.5	1	0.4	4.73	0	4	12.1	11.3	10.5
										1	5.7	13.8		
										2	7.2	15.3		
		PF25 PF42				1.5~2.5	1.8	0.4		3	8.8	17.9		
										0	4.7	12.8		
										1	6.4	14.5		
M3.5*0.6	.138~32 (#6~32)	PF15 PF41	M3.5	632	5.4	1.5~3.2	1.8	0.4	5.38	2	7.9	16	15.3	11.5
										3	9.5	17.6		
										0	6	16.4		
		PF25 PF42				3.2~4.8	3.4	1.6		1	7.6	18		
										2	9.2	19.6		
										3	10.8	21.2		
M4*0.7	.184~32 (#8~32)	PF15 PF41	M4	832	6.75	1.5~3.2	1.8	0.4	6.7	0	6.4	16.9	15.6	13
										1	8	18.5		
										2	9.5	20		
		PF25 PF42				3.2~4.8	3.4	1.6		3	11.1	21.6		
										0	8	18.5		
										1	9.5	20		
M5*0.8	190~32 (#10~32)	PF15 PF41	M5	032	6.75	1.5~3.2	1.8	0.4	6.7	2	11.1	21.6	15.6	13
										0	6.4	16.9		
										1	8	18.5		
		PF25 PF42				3.2~4.8	3.4	1.6		2	9.5	20		
										3	11.1	21.6		
										0	8	18.5		
M6*1	,250~20 (1/4~20)	PF15 PF41	M6	0420	8.2	1.5~3.2	1.8	0.4	8.17	1	9.4	22.1	19.3	14.7
										2	11	2.7		
										3	12.6	25.3		
		PF25 PF42				3.2~4.8	3.4	1.6		0	9.4	22.1		
										1	11	2.7		
										2	12.6	25.3		




PF21/PF22 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PF21 - M3 - 1 - BL

↓ ↓ ↓ ↓

Type Thread Code Screw Length code Optional DuraBlack Finish




尺寸单位: MM
All Dimensions are in Millimeters

螺纹尺寸*螺距 Thread Size*Pitch		型号 TYPE	螺纹码 Thread Code		底端码 Shank Code	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	A	T1	T2	G	C	E
METRIC (公制)	UNIFIED(英制)		METRIC (公制)	UNIFIED(英制)				Max	±0.2	Nom	±0.4	Max	±0.25
M3*0.5	.112~40 (#4~40)	PF21	M3	440	0	1	5.55	0.97	12.3	11.5	4	5.53	10.5
					1				14		5.7		
		PF22			2	1.5		1.47	15.5		7.2		
					3				17.1		8.8		
M3.5*0.6	.138~32 (#6~32)	PF21	M3.5	632	0	1	6.35	0.97	16.4	15.9	5.3	6.33	11.5
					1				18		6.9		
		PF22			2	1.5		1.47	19.6		8.5		
					3				21.2		10.1		
M4*0.7	.164~32 (#8~32)	PF21	M4	832	0	1	7.9	0.97	16.9	16.2	5.6	7.88	13
					1				18.5		7.2		
		PF22			2	1.5		1.47	20		8.7		
					3				21.6		10.3		
M5*0.8	.190~32 (#10~32)	PF21	M5	032	0	1	7.9	0.97	16.9	16.2	5.6	7.88	13
					1				18.5		7.2		
		PF22			2	1.5		1.47	20		8.7		
					3				21.6		10.3		
M6*1	.250~20 (#1/4~20)	PF21	M6	0420	0	1	9.5	0.97	20.5	20	7.1	9.47	14.7
					1				22.1		8.7		
		PF22			2	1.5		1.47	23.7		10.3		
					3				25.3		11.9		

PF30/31/32 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PF31 - **M3** - **30** - **CN**
 ↓ ↓ ↓ ↓
 Type Thread Screw Finish
 Code Length Code
 code



尺寸单位: MM
All Dimensions are in Millimeters


METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	安装孔 Hole Size In Sheet	最小板厚 Min. Sheet Thickness	C	E	G	H	T1	T2	最小边距 Min. Dist Hole C/L
								Max	±0.25	±0.4	±0.13	Nom	Nom	
	M3*0.5	PF31	M3	16、20	0.92	5.5	1	5.48	10.31	7.62	5.13	8.26	15.11	6.6
		PF32			1.38		1.4							
	M4*0.7	PF31	M4	16、18、20	0.92	6.4	1	6.38	11.89	7.62	5.26	8.38	15.24	7.37
		PF32			1.38		1.4							
	M5*0.8	PF31	M5	16	0.92	8	1	7.98	13.46	7.62	5.29	8.51	15.37	8.38
		PF32			1.38		1.4							
	M6*1	PF32	M6	18.5	1.38	9.5	1.4	9.48	15.88	8.89	6.12	9.78	17.15	9.65

尺寸单位: 英寸 All Dimensions are in Inches														
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	安装孔 Hole Size In Sheet	最小板厚 Min. Sheet Thickness	C	E	G	H	T1	T2	最小边距 Min. Dist Hole C/L
								max	±.010	±.015	±.005	Nom	Nom	
	.112-.40 (#4-.40)	PF30	440	30	.030	.203	.030	.202	.406	.300	.202	.325	.###	.26
		PF31			.038		.040							
		PF32			.058		.060							
	.138-.32 (#6-.32)	PF30	632	30	.030	.219	.030	.218	.438	.300	.202	.325	.###	.28
		PF31			.038		.040							
		PF32			.058		.060							
	.164-.32 (#8-.32)	PF30	832	30	.030	.250	.030	.249	.468	.300	.207	.330	.###	.29
		PF31			.038		.040							
		PF32			.058		.060							
	.190-.32 (#10-.32)	PF30	032	30	.030	.312	.030	.311	.530	.300	.220	.335	.###	.33
		PF31			.038		.040							
		PF32			.058		.060							
	.250-.20	PF32	0420	35	.058	.375	.060	.374	.625	.350	.242	.385	.###	.38

PF50/51/52
PF60/61/62
面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PF50 - M3 - 1 - CN
 ↓ ↓ ↓ ↓
 Type Thread Code Screw Length code Finish Code




尺寸单位: MM All Dimensions are in Millimeters														
螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A (Shank) max.	安装孔 Hole Size In Sheet +0.08	最小板厚 Min. Sheet Thickness	C	E	G	H	P	T1	T2
	凸边 Knurled Cap	平边 Smooth Cap												
M3*0.5	PF50	PF60	M3	0	0.77	5.5	0.8	5.48	10.3	5.84 7.37	5.26	0 1.52	8.64	13.21
				1										
	PF51	PF61	M3	0	0.97	5.5	1	5.48	10.3	5.84 7.37	5.26	0 1.32	8.64	13.21
				1										
	PF52	PF62	M3	0	1.48	5.5	1.5	5.48	10.3	5.84 7.37	5.26	0 0.81	8.64	13.21
				1										
M3.5*0.6	PF53	PF60	M3.5	0	0.77	5.56	0.8	5.54	11.1	5.84 7.37	5.26	0 1.52	8.64	13.21
				1										
	PF54	PF61	M3.5	0	0.97	5.56	1	5.54	11.1	5.84 7.37	5.26	0 1.32	8.64	13.21
				1										
	PF55	PF62	M3.5	0	1.48	5.56	1.5	5.54	11.1	5.84 7.37	5.26	0 0.81	8.64	13.21
				1										
M4*0.7	PF56	PF60	M4	0	0.77	6.4	0.8	6.38	11.9	5.84 7.37	5.51	0 1.52	8.64	13.46
				1										
	PF57	PF61	M4	0	0.97	6.4	1	6.38	11.9	5.84 7.37	5.51	0 1.32	8.64	13.46
				1										
	PF58	PF62	M4	0	1.48	6.4	1.5	6.38	11.9	5.84 7.37	5.51	0 0.81	8.64	13.46
				1										
M5*0.8	PF59	PF60	M5	0	0.77	8	0.8	7.98	13.5	5.84 7.37	5.72	0 1.52	8.64	13.46
				1										
	PF60	PF61	M5	0	0.97	8	1	7.98	13.5	5.84 7.37	5.72	0 1.32	8.64	13.46
				1										
	PF61	PF62	M5	0	1.48	8	1.5	7.98	13.5	5.84 7.37	5.72	0 0.81	8.64	13.46
				1										
M6*1	PF62	PF62	M6	0	1.48	9.5	1.5	9.48	15.9	7.11 8.64	6.25	0 1.52	10.04	15.24

尺寸单位: 英寸 All Dimensions are in Inches														
螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	底端码 Shank Code	A (Shank) max.	安装孔 Hole Size In Sheet +0.003	最小板厚 Min. Sheet Thickness	C	E	G	H	P	T1	T2
	凸边 Knurled Cap	平边 Smooth Cap												
.112-40 (#4-40)	PF50	PF60	440	0	.030	.203	.030	.202	.406	.230 .290	.207	.000 .060	.340	.520
				1										
	PF51	PF61	440	0	.038	.203	.040	.202	.406	.230 .290	.207	.000 .052	.340	.520
				1										
	PF52	PF62	440	0	.058	.203	.060	.202	.406	.230 .290	.207	.000 .032	.340	.520
				1										
.138-32 (#6-32)	PF50	PF60	632	0	.030	.219	.030	.218	.438	.230 .290	.207	.000 .060	.340	.520
				1										
	PF51	PF61	632	0	.038	.219	.040	.218	.438	.230 .290	.207	.000 .052	.340	.520
				1										
	PF52	PF62	632	0	.058	.219	.060	.218	.438	.230 .290	.207	.000 .032	.340	.520
				1										
.164-32 (#8-32)	PF50	PF60	832	0	.030	.250	.030	.249	.468	.230 .290	.217	.000 .060	.340	.520
				1										
	PF51	PF61	832	0	.038	.250	.040	.249	.468	.230 .290	.217	.000 .052	.340	.520
				1										
	PF52	PF62	832	0	.058	.250	.060	.249	.468	.230 .290	.217	.000 .032	.340	.520
				1										
.190-32 (#10-32)	PF50	PF60	032	0	.030	.312	.030	.311	.530	.230 .290	.225	.000 .060	.340	.530
				1										
	PF51	PF61	032	0	.038	.312	.040	.311	.530	.230 .290	.225	.000 .052	.340	.530
				1										
	PF52	PF62	032	0	.058	.312	.060	.311	.530	.230 .290	.225	.000 .032	.340	.530
				1										
.250-20 (#1/4-20)	PF52	PF62	0420	0	.058	.375	.060	.374	.625	.280 .340	.246	.000 .060	.395	.600

**PF16/PF26
PF51/PF52
面板螺丝【CAPTIVE SCREW】**

产品型号分解Part Number Designation

PF16 - **M3** - **1** - **BL**
 ↓ ↓ ↓ ↓
 Type Thread Screw Finish
 Code Length Code
 code



尺寸单位: MM
All Dimensions are in Millimeters

螺纹尺寸*螺距 Thread Size*Pitch		型号 TYPE	螺纹码 Thread Code		螺纹码 Thread Code	板厚 Min. sheet Thickness Min Max	A	B	D	G	T1	T2	C	M		
METRIC (公制)	UNIFIED(英制)		METRIC (公制)	UNIFIED(英制)			±0.1	±0.1	±0.8	±0.4	±0.2	Nom	±0.06	Min		
M3*0.5	.112-40 (#4-40)	PF16 PF51	M3	440	0	0-1.6	3.4	2.8	6.4	5.1	13.8	11.9	4.9	9.4		
					1					6.6	15.3					
					2					8.2	16.9					
		PF26 PF52			0	1.6-2.5				4.2	3.6				6.6	15.3
					1										8.2	16.9
M3.5*0.6	.138-32 (#6-32)	PF16 PF51	M3.5	632	0	0-1.6	3.7	2.9	7.2	7.2	17.8	15.4	5.7	10.3		
					1					8.8	19.4					
					2					10.4	21					
		PF26 PF52			0	1.6-2.5				4.5	3.7				8.8	19.4
					1										10.4	21
M4*0.7	.164-32 (#8-32)	PF16 PF51	M4	832	0	0-1.6	4	3.1	8.8	7.3	18.5	16.2	7.3	12		
					1					8.8	20					
					2					10.4	21.6					
		PF26 PF52			0	1.6-2.5				4.8	3.9				8.8	18.5
					1										10.4	20
M5*0.8	.190-32 (#10-32)	PF16 PF51	M5	032	0	0-1.6	4	3.1	8.8	7.3	18.5	16.2	7.3	12		
					1					8.8	20					
					2					10.4	21.6					
		PF26 PF52			0	1.6-2.5				4.8	3.9				8.8	20
					1										10.4	21.6
M6*1	.250-20 (1/4-20)	PF16 PF51	M6	0420	0	0-1.6	4	3.3	10.5	8.8	22.1	20	8.9	13.5		
					1					10.4	23.7					
					2					12	25.3					
		PF26 PF52			0	1.6-2.5				4.8	4.1				10.4	23.7
					1										12	25.3

PFC2/PFS2 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

PFC2

-

M3

-

40

BN

↓

↓

↓

↓


Type

Thread Code

Screw Length code

Finish Code





尺寸单位: MM All Dimensions are in Millimeters																
METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	E	G	H	P	T1	T2	最小边距 Min. Dist Hole C/L To Edge
		钢Steel	不锈钢 Stainless Steel													
	M3*0.5	PFS2	PFC2	M3	40	1.53	1.53	6.73	6.71	7.92	6.4	1.83	0	9.14	###	6.35
					62						9.5		3.2			
	M4*0.7	PFS2	PFC2	M4	50	1.53	1.53	7.92	7.9	9.53	7.9	2.08	0	11.43	###	7.87
					72						11.1		3.2			
					94						14.3		6.4			
	M5*0.8	PFS2	PFC2	M5	50	1.53	1.53	8.74	8.71	10.31	7.9	2.08	0	11.47	###	8.63
					72						11.1		3.2			
					94						14.3		6.4			
	M6*1	PFS2	PFC2	M6	60	1.53	1.53	10.49	10.47	11.89	9.5	2.46	0	14.73	###	9.65
					82						12.7		3.2			
					04						15.9		6.4			

尺寸单位: 英寸 All Dimensions are in Inches																
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号TYPE		螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	E	G	H	P	T1	T2	最小边距 Min. Dist Hole C/L To Edge
		钢Steel	不锈钢 Stainless Steel													
	.112-40	PFS2	PFC2	440	40	.060	.060	.265	.264	.312	.250	.072	.000	.36	.54	.25
					62						.375		.125			
	.138-32	PFS2	PFC2	632	40	.060	.060	.281	.280	.344	.250	.072	.000	.36	.54	.28
					62						.375		.125			
					84						.500		.250			
	.164-32	PFS2	PFC2	832	50	.060	.060	.312	.311	.375	.312	.082	.000	.45	.69	.31+
					72						.437		.125			
					94						.562		.250			
	.190-32	PFS2	PFC2	032	50	.060	.060	.344	.343	.406	.312	.082	.000	.45	.69	.34
					72						.437		.125			
					94						.562		.250			
	250-20	PFS2	PFC2	0420	60	.060	.060	.413	.412	.468	.375	.097	.000	.58	.88	.38
					82						.500		.125			
					04						.625		.250			

PFC2P 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation



PFC2P - M3 - 40

↓
Type

↓

Thead
Code

↓
Screw
Length
code



尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C Max.	E	G	P	T1	T2	槽型尺寸 Driver Size	最小边距 Min. Dis Hole C/ To Edge			
																±0.25	±0.4	±0.64
	M3*0.5	PFC2P	M3	40	1.53	1.53	6.73	6.71	7.92	6.4	0	9.14	13.72	#1	6.35			
			62	9.5						3								
	M4*0.7	PFC2P	M4	50	1.53	1.53	7.92	7.9	9.53	7.9	0	12.19	17.91	#2	7.87			
				72						11.1	3							
				94						14.3	6							
	M5*0.8	PFC2P	M5	50	1.53	1.53	8.74	8.71	10.31	7.9	0	12.45	17.91	#3	8.63			
				72						11.1	3							
				94						14.3	6							
	M6*1	PFC2P	M6	60	1.53	1.53	10.49	10.47	11.89	9.5	0	15.75	22.99	#4	9.65			
				82						12.7	3							
				04						15.9	6							





UNIFIED (英制)

尺寸单位: 英寸
All Dimensions are in Inches

螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +.003	C Max.	E	G	P	T1	T2	槽型尺寸 Driver Size	最小边距 Min. Dis- tance To Edg-
								±.010	±.016	±.025				
.112-40 (#4-40)	PFC2P	440	40	.060	.060	.265	.264	.312	.250	.000	.370	.540	#1	.25
			62						.375	.125				
.138-32 (#6-32)	PFC2P	632	40	.060	.060	.281	.280	.344	.250	.000	.380	.540	#2	.25
			62						.375	.125				
			84						.500	.250				
.164-32 (#8-32)	PFC2P	832	50	.060	.060	.312	.311	.375	.312	.000	.480	.705	#2	.31
			72						.437	.125				
			94						.562	.250				
.190-32 (#10-32)	PFC2P	032	50	.060	.060	.344	.343	.406	.312	.000	.490	.705	#3	.34
			72						.437	.125				
			94						.562	.250				
.250-20 (1/4-20)	PFC2P	0420	60	.060	.060	.413	.412	.468	.375	.000	.620	.905	#4	.38
			82						.500	.125				
			04						.625	.250				

PFHV 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation





尺寸单位: MM
All Dimensions are in Millimeters

METRIC (公制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	E	G	H	P	T1	T2	槽型尺寸 Driver Size	最小边距 Min. Dist Hole C/L To Edge
	M3*0.5	PFHV	M3	0	0.92	0.92	5.5	5.49	6.95	5.55	2.03	0	6.69	11.25	#1	5.8
				1						7.56		1.9				
	M3.5*0.6	PFHV	M3.5	0	0.92	0.92	6	5.98	7.45	6.01	2.34	0	7.45	12.47	#2	6.3
				1						8.42		2.3				
	M4*0.7	PFHV	M4	0	0.92	0.92	6.4	6.38	7.85	6.59	2.79	0	8.5	14.1	#3	6.7
1				9.39						2.7						
尺寸单位: 英寸 All Dimensions are in Inches																
UNIFIED (英制)	螺纹尺寸*螺距 Thread Size*Pitch	型号 TYPE	螺纹码 Thread Code	螺钉长度 Screw Length Code	A A (Shank) Max.	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	E	G	H	P	T1	T2	槽型尺寸 Driver Size	最小边距 Min. Dist Hole C/L To Edge
	.112-40 (#4-40)	PFHV	440	0	.036	.036	.203	.202	.260	216	.080	000	.260	.436	#1	.213
				1						.316		.095				
	.138-32 (#6-32)	PFHV	632	0	.036	.036	.219	.218	.276	.234	.092	.000	.290	.484	#2	.230
				1						.359		.120				

FC 面板螺丝【CAPTIVE SCREW】

产品型号分解Part Number Designation

F C - 3 - 3 BL
 ↓ ↓ ↓ ↓
 Type Thread Code Screw Length code Finish Code



尺寸单位: MM

All Dimensions are in Millimeters



型号TYPE	材质 Materials		板厚 Min.sheet Thickness Min~Max	安装孔 Hole Size In Sheet +0.08	A	B	C	G	D	T1	T2	E	浮动量	
	旋钮	涨铆套			±0.1	±0.1	(Max)	±0.4	±0.3	±0.2		±0.2		
FC-3-1	铝6061- 阳极氧化	铝6061- 本色阳 极氧化	0.8-1.2	4.8	1.0	0.4	4.6	6	1.2	15.3	13.5	###	≥0.6	
FC-3-1B														
FC-3-2			1.5-3.0		1.8	1.0	4.6	6	1.2	15.3	13.5	###	≥0.6	
FC-3-2B														
FC-3-3		不锈钢 12Cr18N i9-表面 钝化	0.8-2.0	4.5	1.2	0.4	4.48	5.5	0.8	14.4	13.4	8.0	≥0.5	
FC-3-3B								5.5		14.4				
FC-3-3B IL								5.5		14.4		7.6	≥0.4	
FC-3-3BL								6.5		15.4		8.0	≥0.5	
FC-3-4		铝6061- 本色阳 极氧化	1.0-1.2	4.8	1.4	0.4	4.6	6	1.0	15.3	13.5	###	≥0.6	
FC-3-4B														
FC-4			2.0-3.5	6.8	2.4	1.0	6.7	8.5		20.0	17.0	###	≥0.9	
FC-4B														
FC-6-1B			1.0-2.0	8.2	1.5	0.4	8.17	12.6		25.3	19.3	###	≥0.9	
FC-6-2B			3.0-4.8		3.4	1.6								

1、当FC-3-2/FC-3-2B用于1.5mm板时，建议B的使用尺寸为0.4。

2、当FC-6-1B用于1.0mm板时，涨铆一侧会出版面0.1-0.2mm,用于1.2mm以上的板无凸出。

PTL2 弹簧定位销【LOCATING PIN, SPRING LOADED】

产品型号分解Part Number Designation





尺寸单位: MM All Dimensions are in Millimeters								
METRIC (公制)	型号TYPE	柱塞直径 Plunger Diameter Code	柱塞长度 Plunger Length code	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	C	D	E1
	PTL2	04	4	1.53	8.33	8.31	6.35	±0.25
	型号	E2	G	H	T1	T2	TR	最小边距
		±0.25	±0.4	±0.13	±0.25	Nom	±0.13	
	PTL2	10.3	7.87	4.32	15.11	22.73	10.92	8.64

尺寸单位: 英寸 All Dimensions are in Inches								
UNIFIED (英制)	型号TYPE	柱塞直径 Plunger Diameter Code	柱塞长度 Plunger Length code	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +.003	C	D	E1
	PTL2	04	4	.060	.328	.327	.250	.50
	型号	E2	G	H	T1	T2	TR	最小边距
		±.010	±.010	±.010	±.010	Nom	±.005	
	PTL2	.406	.310	.17	.595	.895	.430	.34

PT 弹簧定位销【LOCATING PIN, SPRING LOADED】

产品型号分解Part Number Designation



尺寸单位: MM
All Dimensions are in Millimeters


METRIC (公制)	型号TYPE		柱塞直径 Plunger Diameter Code	柱塞长度 Plunger Length code	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +0.08	Max	Max	±0.25	±0.25	±0.4	±0.4	Nom
	钢Steel	不锈钢 Stainless Steel	Code	code			C	D	E1	E2	G	T1	T2
	PT	PTS					56	61	1.53	8.33	8.31	6.35	11.5

尺寸单位: 英寸
All Dimensions are in Inches

UNIFIED (英制)	型号 TYPE		柱塞直径 Plunger Diameter Code	柱塞长度 Plunger Length code	最小板厚 Min. Sheet Thickness	安装孔 Hole Size In Sheet +.003	Max	Max	±0.25	±0.25	±0.4	±0.4	Nom
	钢 Steel	不锈钢 Stainless Steel					C	D	E1	E2	G	T1	T2
	PT	PTS					0.327	.025	0.453	0.405	0.335	0.807	0.740

压铆线扣-TD 【CABLE TIE-MOUNTS】

产品型号分解Part Number Designation



尺寸单位：MM
All Dimensions are in Millimeters

METRIC (公制)	类型TYPE		外形 Shape Size	长度代码 Plunger Length code	长度码 Length Code* L" ±0.08	板厚 Min.sheet Thickness Min~Max	安装孔 Hole Size In Sheet	A	B	C	D	E	G	K	最小 边距 Min
	烧结钢 Steel	不锈钢 Stainles s Steel					+0.05 -0.03	±0.08	±0.15	±0.15	±0.15	±0.15	±0.15	孔边到板边 最短距离	(MI N)
	TD	TDS	40	4	3.07	1.02-1.27	6.35X 3.18	6.25	1.4	1.65	4.06	7.82	3.81	1.02	3.7 3
	TD	TDS	60	6	4.67	1.02-1.78	7.93X 4.75	7.82	1.91	1.65	5.21	9.4	4.57	1.02	4.9 8
	TD	TDS	175	12	9.42	1.02-3.18	12.7X 9.53	12.6	3.3	2.4	9.14	14.28	7.24	1.02	6.6 5



尺寸单位：英寸
All Dimensions are in Inches

UNIFIED (英制)	类型TYPE		外形 Shape Size	长度代码 Plunger Length code	长度码 Length Code* L" ±0.003	板厚 Min.sheet Thickness Min~Max	安装孔 Hole Size In Sheet	A	B	C	D	E	G	K	最小 边距 Min
	烧结钢 Steel	不锈钢 Stainles s Steel					+0.002 -0.001	±.003	±.006	±.006	±.006	±.006	±.006	孔边到板边 最短距离	(MI N)
	TD	TDS	40	4	.121	.040-.050	.250X.125	.246	.055	.065	.160	.308	.150	.040	###
	TD	TDS	60	6	.184	.040-.070	.312X .187	.308	.075	.065	.205	.370	.180	.040	###
	TD	TDS	175	12	.371	.040-.125	.500X.375	.496	.130	.095	.360	.562	.285	.040	###

RAS - M3 - 9 - 6

SMTSO/ SMTSOB 【SURFACE MOUNT NUTS】

产品型号分解Part Number Designation



尺寸单位: MM
All Dimensions are in Millimeters


	螺纹尺寸*螺距 Thread Size*Pitch	通孔 Thru Hole +0.10 -0.08	类型 TYPE		螺纹代码 ThreadC ode	长度代码"L"单位mm Length Code In Mikimeters"L"±0.13				最小板厚 Min.Sheet Thickness	A Max.	C maX.	E		H Nom.	H 安装空 尺寸 Hole Size In Sheet +0.08	D最小焊 盘直径 Min.Sold er Pad
			钢 Steel	黄铜Brsss									Ref.	±0.13			
METRIC (公制)	S1	/	SMTSO	/	M1	1	2	3	/	0.5	0.48	2.41	3.66		3.18	2.5	4.19
	S1.2	/	SMTSO	/	M1.2	1	2	3	/	0.5	0.48	2.41	3.66		3.18	2.5	4.19
	S1.4	/	SMTSO	/	M1.4	1	2	3	/	0.5	0.48	2.41	3.66		3.18	2.5	4.19
	M1.6*0.35	/	SMTSO	/	M1.6	2	3	4	6	0.5	0.48	2.41	3.66		3.18	2.5	4.19
	M2*0.4	/	SMTSO	SMTSOB	M2	3	4	6	8	1.53	1.53	3.6	/	5.56	/	3.73	6.2
	M2.5*0.45	/	SMTSO	SMTSOB	M2.5	3	4	6	8	1.53	1.53	4.09	/	5.56	/	4.22	6.2
	M3*0.5	/	SMTSO	SMTSOB	M3	3	4	6	8	1.53	1.53	4.09	/	5.56	/	4.22	6.2
	M3.5*0.6	/	SMTSO	SMTSOB	M3.5	3	4	6	8	1.53	1.53	5.28	/	7.14	/	5.41	7.77
	M4*0.7	/	SMTSO	SMTSOB	M4	3	4	6	8	1.53	1.53	6.22	/	8.74	/	6.35	9.37
	NA	3.1	SMTSO	SMTSOB	3.1	3	4	6	8	1.53	1.53	4.09	/	5.56	/	4.22	6.2
	NA	3.6	SMTSO	SMTSOB	3.6	3	4	6	8	1.53	1.53	5.28	/	7.14	/	5.41	7.77
	NA	4.2	SMTSO	SMTSOB	4.2	3	4	6	8	1.53	1.53	6.22	/	8.74	/	6.35	9.37

尺寸单位: 英寸
All Dimensions are in Inches

	螺纹尺寸*螺距 Thread Size*Pitch	通孔 Thru Hole +0.04 -.003	类型 TYPE		螺纹代码 ThreadC ode	长度代码"L"单位mm Length Code In Mikimeters"L"±0.13				最小板厚 Min.Sheet Thickness	A Max.	C maX.	E		H Nom.	H 安装空 尺寸 Hole Size In Sheet +0.08	D最小焊 盘直径 Min.Sold er Pad
			钢 Steel	黄铜Brsss		.062	.125	.250	.375				Ref.	±0.13			
UNIFIED(英制)	.060-80 (#0-80)	/	SMTSO	/	080	2	4	/	/	.020	.019	.095	.144	/	.125	.098	.165
	.086-56 (#2-56)	/	SMTSO	SMTSOB	256	2	4	8	12	.060	.060	.142	/	.219	/	.147	.244
	.112-40 (#4-40)	/	SMTSO	SMTSOB	440	2	4	8	12	.060	.060	.161	/	.219	/	.166	.244
	.138-32 (#6-32)	/	SMTSO	SMTSOB	632	2	4	8	12	.060	.060	.208	/	.281	/	.213	.306
	.164.32 (#8-32)	/	SMTSO	SMTSOB	832	2	4	8	12	.060	.060	.245	/	.344	/	.250	.369
	/	.116	SMTSO	SMTSOB	116	2	4	8	12	.060	.060	.161	/	.219	/	.166	.244
	/	.143	SMTSO	SMTSOB	143	2	4	8	12	.060	.060	.208	/	.281	/	.213	.306

平头菊花竖条纹 Flat Head Knurled Body


平头菊花条纹 Flat Head Knurled Body



螺纹 Thread	编号 P/N	T(GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M3	FH-KB-0315	0.5-1.5	6.0	5.0	4.9	8.0	0.8	9.0
	FH-KB-0325	2.0-3.5						11.5
M4	FH-KB-0420	0.5-2.0	6.0	6.0	5.9	9.0	0.8	11.0
	FH-KB-0435	2.0-3.5						12.0
M5	FH-KB-0525	0.5-2.5	7.5	7.0	6.9	10.0	1.0	13.0
	FH-KB-0550	2.5-5.0	8.5					16.0
M6	FH-KB-0630	0.5-3.0	9.2	9.0	8.9	12.3(*13.0)	1.3	15.0(15.5)
	FH-KB-0655	3.0-5.5	10.5					19.5
M8	FH-KB-0835	1.0-3.5	11.5	11.0	10.9	14.5(*16.0)	1.5	18.5
	FH-KB-0860	3.5-6.0						21.0
M10	FH-KB-1040	1.0-4.0	13.5	13.0	12.9	17.0(*19.0)	1.7	21.0
	FH-KB-1065	4.0-6.5						24.0
M10	FH-KB-1035(12H)	1.0-3.5	11.0	12.0	11.9	16.0	1.6	19.0
	FH-KB-1060(12H)	3.5-5.5						24.0
M12	FH-KB-1240	1.0-4.0	13.5	15.0	14.9	18.0	1.7	22.0
	FH-KB-1265	4.0-6.5	14.0					25.0
M12	FH-KB-1240(16H)	1.0-4.0	15.0	16.0	15.9	22.0	2.0	25.0
	FH-KB-1260(16H)	3.5-6.0	16.0					28.0

小沉头竖条纹 Reduce Head Knurled Body


小沉头竖条纹 Reduce Head Knurled Body



螺纹 Thread	编号 P/N	T(GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M3	RH-KB-0320	0.5-2.0	6.2	5.0	4.9	6.0	0.5	9.0
	RH-KB-0335	1.5-3.0						11.5
M4	RH-KB-0420	0.5-2.0	7.0	6.0	5.9	7.0	0.5	11.0
	RH-KB-0440	2.0-4.0						13.0
M5	RH-KB-0520	0.5-2.0	7.0	7.0	6.9	8.0	0.5	11.5
	RH-KB-0540	2.0-4.0						13.0
M6	RH-KB-0625	0.5-2.5	8.5	9.0	8.9	10.0(10.4)	0.6	14.0
	RH-KB-0650	2.5-5.0						16.0
M8	RH-KB-0830	0.5-3.0	10.0	11.0	10.9	12.0(12.4)	0.65	16.5
	RH-KB-0850	3.0-5.0						18.5
M10	RH-KB-1035	1.0-3.5	12.5	13.0	12.9	14.0	0.7	19.5
	RH-KB-1060	3.5-6.0						22.0
M10	RH-KB-1035(12H)	1.0-3.5	12.5	12.0	11.9	13.0	0.7	19.5
	RH-KB-1060(12H)	3.5-5.5						22.0
M12	RH-KB-1240	1.0-4.0	16.2	16.0	15.9	17.6	0.75	24.2
	RH-KB-1260	4.0-6.5					0.8	27.5
M12	RH-KB-1235	0.5-3.5	15.2	15.0	14.9	16.5	0.8	22.0

平头半六角Flat Head Semi-Hex Body


平头半六角 Flat Head Semi-Hex Body



螺纹 Thread	编号 P/N	T(GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M3	FH-SHB-0325	0.5-1.8	5.5	5.0	4.9	8.0	0.75	9.0
M4	FH-SHB-0420 FH-SHB-0440	0.5-2.0 2.0-4.0	7.0	6.0	5.9	9.0	0.8	11.0 13.0
M5	FH-SHB-0525 FH-SHB-0540	0.5-2.5 2.5-4.0	7.5	7.0	6.9	10.0	1.0	13.0 14.0
M6	FH-SHB-0630 FH-SHB-0650	0.5-3.0 3.0-5.0	9.2	9.0	8.9	12.7(*13.0)	1.35	15.0(15.5) 19.5
M8	FH-SHB-0835 FH-SHB-0855	1.0-3.5 3.5-5.5	11.2	11.0	10.9	15.0	1.5	18.0 21.0
M10	FH-SHB-1035 FH-SHB-1060	1.0-3.5 3.5-6.0	12.5 12.8	13.0	12.9	18.0 18.0(*19.0)	1.7	23.0 23.0
M10	FH-SHB-1035(12H)	1.0-3.5	11.0	12.0	11.9	17.0	1.6	19.0
M12	FH-SHB-1250(15H)	1.5-4.0	14.5	15.0	14.9	20.0	1.7	23.0

小沉头内外六角Reduce Hex Head Inner-Hex Body-UK




小沉头内外六角 Reduce Hex Head Inner-Hex Body-UK



螺纹 Thread	编号 P/N	T(GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M4	RHH-IHB-UK-0420	0.5-2.0	6.5	6.0	5.9	7.0	0.5	11.0
M5	RHH-IHB-UK-0525	0.5-2.5	7.5	7.0	6.9	8.0	0.5	12.0*
M6	RHH-IHB-UK-0630	1.0-3.0	9.2	9.0	8.9	10.0*	0.6*	15.5*
M8	RHH-IHB-UK-0835	1.0-3.5	10.5	11.0	10.9	12.0*	0.65*	17.0*
M10	RHH-IHB-UK-1040	1.0-4.0	11.3	13.0	12.9	14.0	0.7	21.0

大沉头菊花竖条纹Countersunk Head Knurled Body

大沉头条纹 Countersunk Head Knurled Body




UNIT(单位): mm




螺纹 Thread	编号 P/N	T(GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M3	CH-KB-0325	1.5-2.5	4.5	5.0	4.9	7.5	1.5	8.5
	CH-KB-0340	2.5-4.0						10.5
M4	CH-KB-0430	1.5-3.0	6.5	6.0	5.9	9.0	1.5	12.0
	CH-KB-0450	3.5-5.0						13.0
M5	CH-KB-0535	1.5-3.5	7.5	7.0	6.9	10.0	1.5	13.0
	CH-KB-0550	3.0-5.0						15.0
M6	CH-KB-0640	1.5-4.0	9.0	9.0	8.9	12.0	1.5	15.5
	CH-KB-0660	4.0-6.0						17.0
M8	CH-KB-0845	2.0-4.5	11.0	11.0	10.9	14.0	1.5	18.5
	CH-KB-0860	4.5-6.0						19.0
M10	CH-KB-1050	2.0-5.0	13.0	13.0	12.9	16.0	1.5	21.0
	CH-KB-1065	3.5-6.5						24.0
M10	CH-KB-1050(12H)	1.6-5.0	11.5	12.0	11.9	15.0	1.5	19.0
	CH-KB-1065(12H)	4.0-7.5						24.0
M12	CH-KB-1250(16H)	2.0-5.0	16.5	16.0	15.9	19.0	1.9	24.0
	CH-KB-1270(16H)	5.0-7.0						24.0

平头（菊花）竖条纹（美标）Flat Head Knurled Body-AVK

平头（菊花）竖条纹（美标） Flat Head Knurled Body-AVK



Thread specifications: Unified 2B/21per ASME B1.1
Metric 6B/21per ASME B1.13M




UNIT(单位): mm



Thread Size	Thread Call Out	Grip Range	Grip Call Out	Hole size +.006 -.000	HD ±.010 ±.205*	HH ±.003	L ±.015	D MAX.	IL MAX.	LB ±.015	ILB MAX.	IATD* MAX.
6-32UNC	632	.020-.080	80	17/64(.2656)	.390	.030	.420	.265	.305	.740	.640	.610
6-32UNC	632	.080-.130	130	17/64(.2656)	.390	.030	.470	.265	.305	.740	.580	.670
8-32UNC	832	.020-.080	80	17/64(.2656)	.390	.030	.420	.265	.305	.740	.640	.610
8-32UNC	832	.080-.130	130	17/64(.2656)	.390	.030	.470	.265	.305	.740	.580	.670
10-24UNC	1024	.020-.130	130	19/64(.2969)	.415	.030	.475	.296	.315	.990	.845	.730
10-24UNC	1024	.130-.225	225	19/64(.2969)	.415	.030	.585	.296	.315	.990	.735	.840
10-32UNF	1032	.020-.130	130	19/64(.2969)	.415	.030	.475	.296	.315	.990	.845	.730
10-32UNF	1032	.130-.225	225	19/64(.2969)	.415	.030	.585	.296	.315	.990	.735	.840
1/4-20UNC	420	.027-.165	165	25/64(.3906)	.500	.030	.580	.390	.380	1.190	1.005	.895
1/4-20UNC	420	.165-.260	260	25/64(.3906)	.500	.030	.680	.390	.380	1.190	.905	1.035
5/16-18UNC	518	.027-.150	150	17/32(.5312)	.685*	.035	.690	.530	.470	1.390	1.175	.995
5/16-18UNC	518	.150-.312	312	17/32(.5312)	.685*	.035	.805	.530	.425	1.390	1.025	1.120
3/8-16UNC	616	.027-.150	150	17/32(.5312)	.685*	.035	.690	.530	.470	1.390	1.175	.995
3/8-16UNC	616	.150-.312	312	17/32(.5312)	.685*	.035	.805	.530	.425	1.390	1.025	1.120
1/2-13UNC	813	.063-.200	200	11/16(.6875)	.865*	.047	1.150	.685	.850	2.365	2.070	1.505
1/2-13UNC	813	.200-.350	350	11/16(.6875)	.865*	.047	1.300	.685	.850	2.365	1.920	1.505
1/2-13UNC	813	.365-.500	500	11/16(.6875)	.865*	.047	1.450	.685	.860	2.365	1.770	1.505

平头竖条纹 (盲孔) Flat Head Knurled Body Close End


平头条纹盲孔铆螺母 Flat Head Rivet Nut With Striations And Blind Holes



螺纹 Thread	编号 P/N	T (GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M4	FH-KBC-0420	0.5-2.0	11.3	6.0	5.9	9.0	0.8	16.0
	FH-KBC-0440	2.0-4.0						18.0
M5	FH-KBC-0530	0.5-2.5	11.5	7.0	6.9	10.0	1.0	17.0
	FH-KBC-0550	2.5-4.5						19.0
M6	FH-KBC-0630	0.5-3.0	13.0	9.0	8.9	12.3	1.3	19.2
	FH-KBC-0650	3.0-5.0						21.0
M8	FH-KBC-0830	0.5-3.0	14.8	11.0	10.9	15.0	1.5	21.5
	FH-KBC-0855	3.0-5.5						24.0
M10	FH-KBC-1040	1.0-4.0	19.2	13.0	12.9	17.0	1.6	27.0
	FH-KBC-1060	3.5-6.0						32.5

平头全六角 Flat Head Full Hex Body

平头全六角 Flat Head Full Hex Body



螺纹 Thread	编号 P/N	T (GRIP RANGE) Min Max	A Rer	Hole size +0.1 0	D +0.07 -0.1	B	K	L
M3	FH-FHB-0325	0.5-1.5	5.5	5.0	4.9	7.5	0.8	8.5
M4	FH-FHB-0420	0.5-2.0	6.5	6.0	5.9	9.0	0.8	11.0
	FH-FHB-0440	2.0-4.0						13.0
M5	FH-FHB-0525	0.5-2.5	8.0	7.0	6.9	10.0	1.0	14.0
	FH-FHB-0540	2.5-5.0						16.5
M6	FH-FHB-0630	0.5-3.0	8.5	9.0	8.9	12.7(*13.0)	1.35	15.0(*16.0)
	FH-FHB-0650	3.0-5.5						19.5
M8	FH-FHB-0835	1.0-3.5	10.5	11.0	10.9	16.0	1.5	18.0
	FH-FHB-0855	3.5-5.5						21.0
M10	FH-FHB-1035	1.0-3.5	12.5	13.0	12.9	18.0(*19.0)	1.7	21.0(*23.0)
	FH-FHB-1060	3.5-6.0						24.0
M10	FH-FHB-1035(12H)	1.0-3.5	13.5	12.0	11.9	18.0	1.7	21.0
	FH-FHB-1040(12H)	3.5-6.0						22.5
M12	FH-FHB-1240(15H)	1.0-4.0	14.0	15.0	14.9	20.0	1.7	23.0
M12	FH-FHB-1250(16H)	2.0-5.0	16.5	16.0	15.9	23.0	2.0	27.0
	FH-FHB-1280(16H)	5.0-8.0						30.0